



Silvery Anodized Aluminum Heat sink Extrusion Profiles , Aluminum Radiator

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



Product Specification

- Product Name: Aluminum Heatsink Extrusion Profiles
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T4, T5, T6 ,T66
- Highlight: **heatsink extrusion profiles, aluminium extrusion heat sink profiles**

for more products please visit us on aluminumextrusion-profiles.com

Product Description

Silvery Anodized Aluminum Heat sink Extrusion Profiles , Aluminum Radiator

Description:

Sun Flower Aluminum Raditors/Aluminum Heat Sink

- (1). Suitable for Industrial Aluminium Profiles.
- (2). 20 years warranty.
- (3). High corrosion resistance.
- (4). 5-10 years weather resistance.
- (5). Good wear resistance & anti-scratch.
- (6).Size customized.

Item	Black Anodized Aluminum Heatsink Extrusion Profiles , Aluminum Radiator
Alloy	6061,6060,6063,6005 etc
Temper	T5, T6
Finishing	Mill finished, Anodized, Electrophoresis, Powder coated, Painted, Sliver matt, Sand blasted, PVDF, Silkscreened etc.
Shape	Round, Square, Triangle, Rectangle etc...and Customized shapes are welcomed.
Technology Supports	1, Engineering design 2, AutoCAD, pro/e ,UG drawing
Standard for Extrusion	GB /T5237-2008 .EN-755-2/3/6/8, BS-1474, BS 1161 (British Standards),JIS H4100 (Japanese Standard),AS/NZS1866-1997 (Australian New Zealand Standard)
Machining & Fabrication	Cutting, Shearing, Deburring, Tumbling, Punching, Drilling, Tapping, Chamfering, Cold-drawing, Honing, Bending, Stamping, Forming, Polishing, Grinding, Brushing, Sandblasting, Welding Numerical Control Lathing, Milling, Sophisticated CNC Precision Machining
Packing method	1. Standard packing: Eachprofile will be wrapped in the EPE sheet in order to protect the profiles' surfaces, kraft paper wrapped in bundles. 2. Special packing: wooden cases 3. pallet 4. EPE+carton box+pallet or wooden case 5. Customized packing methods are welcomed. 6.13 tons to a 20 feet container, 20 tons to a 40 feet container

Order,payment,terms,shipment

- 1, Minimum order: 500 kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.)Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment :30% T/T in advance the balance after the copy of BOL .

Application:

We manufacture all kinds of aluminum profiles,including:

1. Aluminum profile for architecture
2. Aluminum profile for window and door
3. Aluminum profile for curtain wall
4. Aluminum profile for glass wall
5. Aluminium profile for furniture
6. Aluminum profile for closet wardrobe door
7. Aluminum profile for kitchen cabinet
8. Aluminium profile for decoration
9. Aluminium profil for industry
10. Aluminum profile for handrail
11. Aluminium profile for solar panel
12. Aluminum flat,square,round tube
13. Aluminum profile for louver/shutter
14. Aluminum window and door
15. Wood gain aluminum profile
16. Aluminum profile for LED strip,transportation rail,ten etc.
17. OEM service can be provide

Product fabrication though machining milling, drilling, cutting and welding for different size and shape; and surface treatment for anodize, powder coating, polishing, brushing etc.

Specifications:

1. Primary Technical Data

1) Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%



Competitive Advantage:

- 1, We can do the designs according to the customers' requirement
- 2, We can open customers' own die as per their requirement
- 3, We can offer you the high quality products & reasonable price
- 4, We can offer you a good after-sell service
- 5, We have strong professional design team
- 6, Prompt delivery, sample order is welcome.



HENTEC Hentec Industry Co.,Ltd

+86-13861643436

aluminum@hentec.com.cn

aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421