Silding / Casement Aluminum Window Frame Extrusions Profiles With Deep -Processing

Basic Information

- Place of Origin:
- Brand Name:
- CA ,CE Certification:
- Minimum Order Quantity: 1 ton
- Packaging Details: EP Paper ,kraft and pallet 20days

China HT

T/T or L/C

100 000 ton each month

- Delivery Time:
- Payment Terms:

Product Specification

- Supply Ability:
- Material:
- Temper:
- Alloy:
- Surface:
- Color:
- Application:
- Highlight:

Aluminum

Τ5

- 6063 / 6061 / 6060
- Powder Painted
- Customerized
- Window
- aluminum extrusion profiles, extruded aluminium profiles



for more products please visit us on aluminumextrusion-profiles.com

Silding / Casement Aluminium Window Extrusion Profiles With Deep - Processing

Descrition:

- 1, Product: slide profile, extruded aluminium profile,
- 2, Alloy: Al 6063, 6061,6005,6060
- 3, Execute standard: ASTM B221, EN755, GB5237. GB6892.
- 4, Surface treatment: Anodize, powder coating, electrophoresis coating, polished, brushed, PVDF coating, spray wood, electrophoresis wood, etc;
- 5, Colour: Sliver, champagne, gold, green, wood, etc;
- 6, Qualification: ISO 9001; 7, Length: 6-7m(or clients' requests).

Specifiaction of High Quality Aluminum Profile:

Specifiaction of high	Quality Aluminum Frome.						
Description	aluminum profile windows and door						
Material Thickness(t)	terial Thickness(t) t=1.0 / 1.2 / 1.4						
Material	Aluminum Alloy 6063, 6061						
Annealing Treatment	aling Treatment T5,T6						
Color	Green, Grey, Black, White, (RAL series)etc.						
Surface Treatment	Mill finish, anodized, powder coated, electrophoresis, sand balsting etc.and depend on customer's demand.						
Shape	Square, Round, Flat, Oval, and according to customer's drawing.						
Length	Normal length=6m or in customer's request						
Usage	Building, Production Line, Decoration, Industrial, Transportation, Door and window, etc.						
Package	 Pearl cotton foam for each aluminum profile ; Wrap with shrink film exterior; Packed according to customer request. 						
Advantages/Features	Providing colorful products with various mechanical performances to adapt all kinds of architectural styles						

Power Coating aluminum profile windows and door



Applications:

Aluminum profile used for making aluminum door . There are many colors can be selected for surface treatment . The strength can be increased by higher wall thickness . It is possible to produce according to customized design .



Specifications:

1. Primary Technical Data

r) Chemical composition											
	Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
	6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
	6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
	6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
	6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	Т5	≥ 160Mpa	≥ 110Mpa	≥8%
0000	Т6	≥ 205Mpa	≥ 180Mpa	≥8%
6061	Т6	≥ 265Mpa	≥ 245Mpa	≥8%

Competitive Advantage:

- 1. Top Aluminium profile manufacturer for more than 10 years in China.
- 2. Diverse Products used in the fields of construction, industry and deep-processing.
- 3. Quality Control is put in the core position of our production.
- 4. Customized Production shows our capability in product design and process control.
- 5. Perfect Customer Services include careful packaging, quick delivery and good after-sale service.

