Our Product Introduction



T5, T6 Temper Silvery Industrial Aluminium Profile Electroinic Cover

Basic Information

. Place of Origin: China . Brand Name: Hentec SGS · Certification: Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Industrial Aluminium Profile

• Alloy: 6063,6061 • Material: Aluminum

Suface Treatment: ,Anodized ,Electrophoretic Coated,Powder

Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

T5, T6 • Temper:

· Highlight: aluminum extrusion profiles,

aluminium door frame

Product Description

Silvery Anodizing Industrial Aluminium Profile Electrical Cover / Shell / Electroinic Cover

Hentec Industrial Co.,Ltd is professional serves for Building doors and windows profiles, Railway, Cars with aluminum, IT computer, Communications, Electrical, Mechanical, High-speed rail transportation, Refrigerated containers etc., special aluminum profiles for 17 years.

N o.	Name	Description	Re mar k
1	Product series	Wardrobe door series, extruded aluminium profile,	
2	Alloy	Al 6063, 6061	
3	Execute standard	ASTM B221, EN755, GB5237. GB6892.	
4		Anodize, powder coating, electrophoresis coating, polished, brushed, PVDF coating, spray wood, electrophoresis wood, etc;	
5	Colour	Sliver, white, champagne, black, gold, green, red, wood, etc;	
6	Qualificati on	ISO 9001;	
7	Length	5.85m(or clients' requests).	

Surface treatment			
Power Coating Profile	As an environment-friendly high quality solvent-free decoration material, our power coated aluminium profile is characterized by excellent corrosion resistance, superior mechanical properties, impact resistance and fine flexibility, uncomparable by ordinary aluminum products, resistant to ultraviolet light, free from fading and influence from harsh weather, and lasting color and gloss		
Wood Grain Profile	As a leading environment-friendly domestic building aluminium product, the wood-grain aluminium product contributes to modern home decoration. With all the advantages of centralized coated aluminium products, it has wood-like visual effects. It outweighs the wood products in terms of fireproof and thermal insulation and corrosion resistance.		
Thermal-Break Profile	With sealed thermal and cold insulation performance, the thermal break aluminium product can significantly reduce energy consumption, in compliance with the requirements of the national energy-saving decree. It also has good characteristics to resist the erosion caused by harmful.		
PVDF Profile	Our fluorocarbon coated aluminium profile is characterized by the smooth surface, uniform color, strongly resistant from high acid, alkali, impact and abrasion. It can with stand long-term strong ultraviolet radiation and acid erosion, free from coating chalking, fading and shedding.		

Order,payment,terms,shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.)Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment: (Can negotiate with customers, our usual practices are as follow)
- 4, Tooling:100% prepaid by T/T.
- 5, Parts:30% upon order confirmation and balance before delivery by T/T

Applications:

Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed. In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

FAQ For Saving Your Precious Time!

- Q1: What's the thickness for anodizing? Can you do 15um?
- A: Our normal thickness is about 10 um. Yes, we can do 15um and above.
- Q2: What color you can do for powder coating? The thickness for powder coat?
- A: We can do any color for powder coat as long as you can provide the color sample. Our normally powder coating thickness is 60-80um.
- Q3: What color you can do for wood grain?

A:Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc.If you need any other colors, we can do according to the color samples you provide.

- Q4: How's the weather resistance for wood grain finish D1010?
- A: (1). Powder:Akzo Noble Interpon D1010.
- (2). Wood grain film:Italian Menphis.

- (3). Standard complied: American AAMA Standard. 2603
- (4). UV test:1000 hours.
- (5). Salt spraying test:1000 hours.
- (6). Normal weather:10 years color guarantee.

Q5: What certification do you have? What's your standard? A:We have ISO certification. Our standard is DIN, AAMA, AS/NZS, China GB.

Q6: What's the delivery time for samples and mass production?

A: (1).2-3 weeks to make the new moulds and make free samples.

(2).3-4 weeks after receipt of deposit and confirmation of the order.

⇒HENTEC Hentec Industry Co.,Ltd



+86-13861643436



aluminum@hentec.com.cn



aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421