



## OEM Construction Anodized Aluminum Extrusion Profile Tolerance 0.02mm

### Our Product Introduction

#### Basic Information

- Place of Origin: China
- Brand Name: Hentec
- Certification: SGS
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



#### Product Specification

- Product Name: Industrial Aluminium Profile
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T4, T5, T6 ,T66
- Highlight: **aluminium extruded profiles,  
aluminum extruded shapes**

## Product Description

**OEM Anodized Aluminum Extrusion Profile , Construction aluminum extruded shapes**

**Satin Anodized Aluminum Extrusion Profile , Aluminum Construction Profile Extrusion Customized Sections**

**Our 4500T grade extrusion machine enable us to produce any section within 400\*150mm and  $\phi$ 360. Your drawings are definitely welcomed.**

### Product Description

Product Description

- (1). Material: Aluminum
- (2). Surface Finished: Polishing ,Anodizing ,Powder Coating etc.
- (3). Process: CNC Turning ,Milling ,Casting ,Cold Forging ,etc.
- (4). Tolerance:0.02mm

Parts Information:

- (1). Applicable Material---Aluminum/zinc alloy, iron, steel alloy, plastic, brass, steel, and stainless steel.
- (2). Surface treatment---polishing, zinc plating, nickel plating, chrome plating, anodizing.
- (3). Payment Terms: 40% deposit before production and 60% balance before shipping.
- (4). Packaging: Standard package/ Pallet or container/ as per customized specifications.
- (5). Shipment Terms: Express & air freight is preferred / sea freight/ as per customized specifications.

Alloy	6060	6063	6061	6005A		
Temper	T66	T5/T6	T6/T651			
Standard	EN755-9;DIN	GB5237-2008 EN755-3/DIN ASTMB221				
Certification	ISO9001-2008					
Surface	Anodized, powder coated,wooden grain,polished,brushed, PVDF Coating.					
Color	Anodizing	Silver, bronze, champagne, titanium, nickel, golden yellow, etc The anodized film thickness is over 10um				
	Powder coating	White, Black, Grey,Green, Blue, Yellow , Red and etc. The powder coated thickness is over80um.				
	Wooden grain	USA 3M and Italian MENPHIS transfer printing paper.				
		AKZO NOBEL INTERPON D1010(10 years warranty): Australia cedar, Bush cherry, Chest nut, Jarrah I, Jarrah II, Western red cedar, etc.				
		AKZO NOBEL INTERPON D34(5 years warranty): Bush wood, Western red, Jarrah, Snow gum, etc.				
Deep processing	Fabrication	90degree, 45degree and any degree Cutting, punching, drilling, bending, weld, mill, CNC, etc.				

### Order,payment,terms,shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab. )Production Lead time: it depends on customers' order quantity ( 30 working days after deposit).
- 3, Payment: (Can negotiate with customers, our usual practices are as follow)
- 4, Tooling:100% prepaid by T/T.
- 5, Parts:30% upon order confirmation and balance before delivery by T/T

### Applications:

Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

### Competitive Advantage:

1. good quality aluminium profile with economic price
2. 15-year manufacturing experience
3. ISO9000
4. ODM or OEM



#### FAQ For Saving Your Precious Time!

Q1:What's the thickness for anodizing?Can you do 15um?

A:Our normal thickness is about 10 um.Yes, we can do 15um and above.

Q2:What color you can do for powder coating?The thickness for powder coat?

A:We can do any color for powder coat as long as you can provide the color sample.Our normally powder coating thickness is 60-80um.

Q3:What color you can do for wood grain?

A:Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc.If you need any other colors, we can do according to the color samples you provide.

Q4:How's the weather resistance for wood grain finish D1010?

A:(1).Powder:Akzo Noble Interpon D1010.

(2).Wood grain film:Italian Memphis.

(3).Standard complied:American AAMA Standard.2603

(4).UV test:1000 hours.

(5).Salt spraying test:1000 hours.

(6).Normal weather:10 years color guarantee.

Q5:What certification do you have?What's your standard?

A:We have ISO certification.Our standard is DIN, AAMA, AS/NZS, China GB.

Q6:What's the delivery time for samples and mass production?

A:(1).2-3 weeks to make the new moulds and make free samples.

(2).3-4 weeks after receipt of deposit and confirmation of the order.

**HENTEC** Hentec Industry Co.,Ltd

+86-13861643436

aluminum@hentec.com.cn

aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421