



Customized Anodized Extruded Alloy Profile With Powder Coated / Wooden Grain

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HENTEC
- Certification: SGS
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



Product Specification

- Highlight: aluminium extrusion profiles,
aluminium extruded profiles

for more products please visit us on aluminumextrusion-profiles.com

Product Description

Customized Anodized Aluminum Extrusion Profile / Extruded Alloy Profile

- With perfect surface performance
- Machining available according to **Customized Design**.

Description	Aluminum architecture extrusion profile	
Alloy/Temper	6063-T5/6060-T5; 6063-T6/6060-T6	
Surface treatment	Mill finishes; Anodized; Powder coated; Wooden grain, Machine/Acid polished and etc	SGS TEST APPROVAL
Standard apply	EN755; DIN; ASTM B221; GB5237-2008 and etc	SGS TEST APPROVAL
Price	SMM/LME Primary aluminum price + the most competitive conversion cost	
Mould policy	Each item purchased volume get to 3tons, refund mould payment	
Delivery timetable	sample: within 15 days; order: within 15 -20 days	SGS TEST APPROVAL
Payment term	20% deposit, the balance pay against B/L copy within 7 days	SGS TEST APPROVAL
Packing standard	Protected film and pearl cotton inside and shrink film outside	SGS TEST APPROVAL
Guarantee term	If the shipped products can not meet required, the total order amount will be refund back without delay, or arrange new replacement cargoes instead	SGS TEST APPROVAL

Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

Specifications:

1.Primary Technical Data

1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

Competitive Advantage:

- WHO ARE WE

1. **Top Aluminium** profile manufacturer for 20 years in China.
2. **Diverse Products** used in the fields of construction, industry and deep-processing.

- WHY CHOOSE US

1. **Quality Control** is put in the core position of our production.
2. **Customized Production** shows our capability in product design and process control.
3. **Perfect Customer Services** include careful packaging, quick delivery and good after-sale service.

- WHERE DO WE EXPORT

1. **North America:** USA, Canada.
2. **South America:** Brazil, Argentina, Chile, etc.
3. **Europe:** Spain, France, Germany, The Netherlands, Russia, etc.
4. **Aisa and Oceania:** Vietnam, Thailand, India, Australia, etc.
5. **Total 53 countries.**



 **HENTEC** Hentec Industry Co.,Ltd

 +86-13861643436

 aluminum@hentec.com.cn

 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421