


Sunflower Heat Sink / Aluminum Heatsink Extrusion Profiles For Led Light

Basic Information

- Place of Origin:
- Brand Name:
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep pap
- Delivery Time:
- Payment Terms:
- Supply Ability:



China HENTEC

100 000ton each month



Product Specification

- Product Name:
- Alloy:
- Material:
- Suface Treatment:
- Deep Process:
- Temper:
- Highlight:

Aluminum Heatsink Extrusion Profiles
6063,6061,6005
Aluminum
Mill Finished, Anodized, Electrophoretic

- Coated, Powder Spray Coated
- Milling, Drilling, Bending, Cutting
- T4, T5, T6
 - aluminium heatsink extrusion, aluminium extrusion heat sink profiles



Sunflower Heat Sink / Aluminum Heatsink Extrusion Profiles For Led Light

Our Advantages:

1. 17+ years experience in providing ONE-STOP customized aluminium extrusion and machining solution; 11+ years of exporting to 40+ countries;

2. ISO: 9001:2008, RoHS, SGS, Reach, D&B

- 3. 100% new material
- 4. Competitive prices with short lead-time for both tooling and parts, because we do everything in-house
- 5. Effective and strong technical support (30+ engineers) and excellent sales services .
- 6. Sufficient production capacity (22 extrusion lines; 3+ CNC machines).

Material	6000 series Aluminium					
Temper	Т4, Т5, Т6					
	General profiles thickness from 0.8 to 5.0mm,					
Size /	length from 3m-6m or customized available;					
Thickness	Anodize protection film thickness from 8~25 um,					
	powder coating from 40 ~ 120 um.					
Shape	square, round, rectangular, special shape customized					
	- for LED lighting Frame					
	- for Motor Shell					
	- for Hook of LED Stage lighting					
Application	- for Industry assembly lines equipment.					
	- for Heat sinks(such as: LED lighting, Car Audio Shell, High-power LED					
	Street lighting, LED tunnel lighting and so on.)					
	 other by custom design size and dimension 					
Surface	powder coating, electrophoresis, wood grain , anodized					
reatment	Fluorocarbon Spraying, Sand blast, Polished, Brushed and so on					
Colors	Ref: powder coating color sheet and customized color available					
Deep process	CNC, drilling, milling, cuttin, punching, bending, assembling					
MOQ	1000 kgs for each item, usually 13-15 tons for a 20GP, 25-28 tons for a 40HQ.					
Packing Details	(1)Inside : packed with EP Foam protective film to protect each piece					
Packing Details	(2) Outside: Wrap to be bundles by waterproof craft paper					
	(1)Die Developing and Sample testing: 12-18 days .					
Delivery time	(2) Mass Production completed: 20-30days after sample is confirmed by					
	Buyer.					
FOB Port	Shanghai					
payment terms	T/T 30% for deposit, balance before shipping.					
settlement term	Charge by final actual weight or by drawing theoretical weight.					
Certificate and	SGS, ISO available					
Standard	GB5237-2008 equal to EN12020-1.2 (2001)					

Applications:

Aluminum heat sink is widely used on Machines , cars , lighter ...

Specifications:

1. Primary Technical Data 1)Chemical composition

r)one	r)chemical composition									
Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥8%
0000	Т6	≥ 205Mpa	≥ 180Mpa	≥8%
6061	Т6	≥ 265Mpa	≥ 245Mpa	≥8%



Competitive Advantage: We can offer professional Manufacturing and exporting service, OEM/ODM for Metal & Plastic parts in China. All the parts manufactured by CNC Lathe & Milling Machine Center.



Tag : LED Aluminum Heat Sink extruded aluminum heat sink

HENTEC Hentec Industry Co.,Ltd

& +86-13861643436

aluminum@hentec.com.cn (2) aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421