



## Custom Industrial Aluminum Profile / Aluminium Angle Profile / LED Profile

### Our Product Introduction

for more products please visit us on [aluminumextrusion-profiles.com](http://aluminumextrusion-profiles.com)

#### Basic Information

- Place of Origin: China
- Brand Name: Hentec
- Certification: SGS
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 50 000ton each month



#### Product Specification

- Product Name: Industrial Aluminium Profile
- Alloy: 6063,6061,6005
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Cutting
- Temper: T5, T6
- Usage: Industrial
- Highlight: **aluminum extrusion profiles,  
aluminium door frame**



## Product Description

### Custom Industrial Aluminum Profile / Aluminium Angle Profile / LED profile

#### Product Description

Technology	Aluminum extrusion
Surface treatment	Mill finish, anodizing, powder coated, sandblasting, electrophoresis etc
Color	Silvery white, black, golden, champagne, dark bronze or according to your requirement
Normal anodizing thickness	8-20 um
Normal power coating thickness	60-100 um
Shape	Square, Round, Flat, or according to customers' drawings
Deep processing	Cutting, drilling, punching, bending ,CNC,tapping etc
2D&3D Design	1.4Designers in design and development department
	2.Auto CAD, 3D, AI, SLD, PRT. IGS, PDF, JPEG etc.
Engineering& tooling	1.8 Engineers in Mold Shop.
	2. Use high tonnage extruder, Wire EDM, CNC, Drilling machines etc.
Quality control	1.Inspection at Site.
	2.Inspection Before Shipping.
Packing details	3.Packed according to customer request.
	1. Pearl cotton foam for each profile;
	2. Wrap with shrink film exterior;
Delivery	3. Packed according to customer request.
	15-25days after receiving the deposit
Payment Term	T/T, L/C

#### Competitive Advantage:

1. good quality aluminium profile with economic price
2. 15-year manufacturing experience
- 3 .ISO9000
4. ODM or OEM



#### FAQ For Saving Your Precious Time!

Q1:What's the thickness for anodizing?Can you do 15um?

A:Our normal thickness is about 10 um.Yes, we can do 15um and above.

Q2:What color you can do for powder coating?The thickness for powder coat?

A:We can do any color for powder coat as long as you can provide the color sample.Our normally powder coating thickness is 60-80um.

Q3:What color you can do for wood grain?

A:Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc.If you need any other colors, we can do according to the color samples you provide.

Q4:How's the weather resistance for wood grain finish D1010?

A:(1).Powder: Akzo Noble Interpon D1010.

(2).Wood grain film:Italian Memphis.

(3).Standard complied:American AAMA Standard.2603

(4).UV test:1000 hours.

(5).Salt spraying test:1000 hours.

(6).Normal weather:10 years color guarantee.

Q5:What certification do you have?What's your standard?

A:We have ISO certification.Our standard is DIN, AAMA, AS/NZS, China GB.

Q6:What's the delivery time for samples and mass production?

A:(1).2-3 weeks to make the new moulds and make free samples.

(2).3-4 weeks after receipt of deposit and confirmation of the order.