



## Black Anodized Aluminum Solar Panel Frame 6063 - T5 With Customized Size

Our Product Introduction

for more products please visit us on [aluminumextrusion-profiles.com](http://aluminumextrusion-profiles.com)

### Basic Information

- Place of Origin: China
- Brand Name: HENTEC
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: Packed with EP ,Carton ,Pallet or wooden case
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 3000tons each month



### Product Specification

- Product Name: Aluminum Solar Panel Frame
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T4, T5, T6
- Highlight: **anodized aluminum frame,  
solar panel aluminum frame**

## Product Description

### Black Anodized Aluminum Solar Panel Frame 6063 - T5 With Customized Size

- 1) CNC cutting: 8 sets
- 2) CNC lathe: 7 sets
- 3) CNC machining center: 4 sets
- 4) CNC EDM: 14 sets.
- 5) Extrusion lines: 44 sets imported from Japan, Italy with annual capacity 400 thousands of tons.
- 6) With 5 full-automatically horizontal type and 1 vertical type.
- 7) The oxidize aluminum materials length is up to 10m, electrophoretic materials length is up to 7.5m, with an annual output of 150,000 tons.
- 8) With 4 powder coating lines from Italy.

#### More Information:

|                           |  |
|---------------------------|--|
| <b>Item</b>               | Aluminum Solar Panel Frame with Customized Size and Color  |
| <b>Material</b>           | Aluminium 6000 series alloy: such as 6063 6005 6061  |
| <b>Temper</b>             | T4 T5 T6   |
| <b>length</b>             | 3-6 Meter per piece, or as your inquire  |
| <b>Shape</b>              | Round, square, flat, hollow, oval, triangle, U-profile, L-profile, T-profile, customized available |
| <b>Thickness</b>          | General profile Thickness: 0.7 - 5.0mm   |
| <b>Deep process</b>       | CNC ,drilling ,milling ,cutting ,bending ,tapping ,welding ,assembling ,punching                   |
| <b>Frame Section Size</b> | 30mm*35mm ,35mm*35mm ,35mm*40mm , 35mm*45mm ,35mm*50mm etc   |



#### Our Advantages :

1. 22 years' experiences of manufacturing .
2. STRONG R&D: Help customers finalize the design, strong tool design ability, excellent pressing and surface treatment technology.
3. Strict quality management: ISO Administration system.
4. 24 hours on-line communication. Professional, Patient, Flexible.
5. High capacity of manufacturing and wide range of products.
6. Be able to provide secondary fabricating.
7. Small order is accepted.
8. Be able to provide one-stop supply solution.
9. Multiple payment methods: TT, LC, DP, OA.

| 新图号<br>旧图号                | 简 图 | 线密度<br>kg/m | 新图号<br>旧图号    | 简 图 | 线密度<br>kg/m |
|---------------------------|-----|-------------|---------------|-----|-------------|
| GT001<br>G701             |     | 0.987       | GT007<br>G007 |     | 0.803       |
| GT002<br>角码为GT001<br>G702 |     | 0.530       | GT008<br>G008 |     | 0.633       |
| GT003<br>G795             |     | 0.615       | GT009<br>G009 |     | 0.494       |
| GT004<br>G794             |     | 0.466       | GT010<br>G010 |     | 0.496       |
| GT005<br>G590             |     | 0.814       | GT011<br>G011 |     | 0.388       |
| GT006<br>G591             |     | 0.681       | GT012<br>G012 |     | 0.290       |

| 新图号<br>旧图号    | 简 图  | 线密度<br>kg/m | 新图号<br>旧图号    | 简 图  | 线密度<br>kg/m |
|---------------|--|-------------|---------------|--|-------------|
| GT013<br>G778 |   | 0.372       | GT019<br>G599 |   | 0.665       |
| GT014<br>G594 |   | 0.367       | GT020<br>G846 |   | 0.400       |
| GT015<br>G595 |   | 0.183       | GT021<br>Z081 |   | 0.884       |
| GT016<br>G596 |   | 0.248       | GT022<br>Z082 |   | 1.228       |
| GT017<br>G597 |   | 0.534       | GT023<br>Z083 |   | 0.952       |
| GT018<br>G598 |  | 0.339       | GT024<br>Z084 |  | 1.073       |

线密度仅供参考，出货以实际称重为准！      210

| 新图号<br>旧图号        | 简图 | 线密度<br>kg/m | 新图号<br>旧图号        | 简图 | 线密度<br>kg/m |
|-------------------|----|-------------|-------------------|----|-------------|
| GT025<br>角码为GT026 |    | 0.653       | GT031             |    | 0.548       |
| G895              |    |             | G893              |    |             |
| GT026             |    | 0.732       | GT032             |    | 0.279       |
| G896              |    |             | G894              |    |             |
| GT027<br>角码为GT026 |    | 0.424       | GT033             |    | 1.711       |
| G915              |    |             | G913              |    |             |
| GT028<br>角码为GT026 |    | 0.524       | GT034<br>角码为GT033 |    | 0.745       |
| G916              |    |             | G914              |    |             |
| GT029             |    | 1.300       | GT035             |    | 0.398       |
| G822              |    |             | G222              |    |             |
| GT030<br>角码为GT029 |    | 0.567       | GT036             |    | 0.754       |
| G823              |    |             | G224              |    |             |

| 新图号<br>旧图号                | 简 图 | 线密度<br>kg/m | 新图号<br>旧图号        | 简 图 | 线密度<br>kg/m |
|---------------------------|-----|-------------|-------------------|-----|-------------|
| GT037<br>G229             |     | 0.172       | GT052             |     | 0.728       |
| GT038<br>G230             |     | 0.374       | GT054<br>角码为GT052 |     | 0.509       |
| GT039<br>G889             |     | 0.626       | GT055<br>角码为GT052 |     | 0.537       |
| GT040<br>G888             |     | 0.756       | GT061             |     | 0.161       |
| GT041<br>角码为GT026<br>G187 |     | 0.692       | GT062             |     | 0.340       |
| GT042<br>角码为GT026<br>G789 |     | 0.443       | GT063             |     | 0.209       |

| 新图号       | 简图 | 线密度<br>kg/m |
|-----------|----|-------------|
| 旧图号       |    |             |
| GT064     |    | 0.394       |
| GT068     |    | 0.497       |
| GT069     |    | 0.613       |
| GT070     |    | 0.312       |
| 角码为 GT050 |    |             |
| GT071     |    | 0.687       |
| GT072     |    | 0.378       |

| 新图号       | 简图 | 线密度<br>kg/m |
|-----------|----|-------------|
| 旧图号       |    |             |
| GT076     |    | 0.698       |
| 角码为 GT050 |    |             |
| GT077A    |    | 0.848       |
| GT078A    |    | 0.635       |
| GT079     |    | 0.524       |
| GT080     |    | 0.651       |
| GT081     |    | 0.395       |

**213** 线密度仅供参考, 出货以实际磅重为准!

HD太阳能系列型材图      国家免检

| 新图号<br>旧图号 | 简 图 | 线密度<br>kg/m |
|------------|-----|-------------|
| GT082      |     | 0.245       |
| GT083      |     | 0.267       |
| GT084      |     | 0.519       |
| GT085      |     | 0.646       |
| GT086      |     | 0.674       |
| GT087      |     | 0.655       |

| 新图号<br>旧图号         | 简 图 | 线密度<br>kg/m |
|--------------------|-----|-------------|
| GT088              |     | 0.677       |
| GT089              |     | 0.558       |
| GT091<br>角钢为 GT092 |     | 0.580       |
| G791               |     |             |
| GT092              |     | 0.967       |
| G792               |     |             |
| GT093<br>角钢为 GT094 |     | 0.832       |
| GT094              |     | 1.519       |

线密度仅供参考，出货以实际磅重为准！ **214**

**Applications:**

- 1) Living house and home building.
- 2) Commercial building, factory, shopping mall, school, stadium etc.
- 3) Power station, field operation and some huge engineer construction.

**Competitive Advantage:**

In addition to high quality ,we at Hentec office offer customer complete service .Our aluminum solar frame comes with a 15 year warranty .Maintenance service is also available .



**HENTEC** Hentec Industry Co.,Ltd

+86-13861643436

aluminum@hentec.com.cn

aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421