Hentec Industry Co.,Ltd aluminumextrusion-profiles.com

OEM Industrial Aluminium Profile System V Slot Aluminum Extrusion Profile

Basic Information

• Place of Origin: China

• Brand Name: HENTEC,KUNTAI


• Certification: CA ,CE ,ISO14001:2004, ISO9001:2000

Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20daysPayment Terms: T/T ,L/C

Supply Ability: 100 000ton each month



Product Specification

Product Name: Industrial Aluminium Profile

Alloy: 6063 ,6005,6060Material: Aluminum

• Suface Treatment: Mill Finished, Anodized , Electrophoretic

Coated, Powder Spray

Coated, Drawbench, Steel Polished

• Deep Process: Milling, Drilling, Bending, Cutting

• Temper: T5, T6

• Highlight: aluminum extrusion profiles,

aluminium extruded profiles

OEM Aluminium Profile System , Industrial Aluminum Profile, V - Slot Aluminium Extrusion Profile

Product Specification

Product Description

- (1). Suitable for T slot aluminum profile
- (2). 20 years warranty.
- (3). High corrosion resistance.
- (4). 5-10 years weather resistance.
- (5). Good wear resistance & anti-scratch.
- (6). Size customized.

| Material | Aluminium 6000 series alloy, such as 6061, 6063, 6082 etc. | | | | |
|-----------------------------|---|--|--|--|--|
| Temper | T4, T5, T6 | | | | |
| Size | 3m-6m per piece, or customized. | | | | |
| Shape | Square, flat, round, hollow, oval, triangle, U-profile, L-profile, T-profile, H-profile, customized available. | | | | |
| Surface Treatment | Mill-finish, anodized, powder coated, electrophoresis, wood grain, timber, PVDF paint, polishing, brushed. | | | | |
| Color | Silver, champagne, black, bronze, gold, white or customized | | | | |
| Application | Window and door with thermal break strips, curtain wall, glass wall, furniture, ceiling, kitchen, LED strip, transportation rail, vehicle, motor housing, machine, tent, solar panel, industrial profile, decoration profile etc. | | | | |
| Deep Process | CNC, drilling, milling, cutting, tapping, welding, bending, assembling. | | | | |
| MOQ | 500 kgs for each item, usually 13-15 tons for a 20GP, 25-28 tons for a 40HQ. | | | | |
| OEM service | Drawing, sample or design service offer by customer. | | | | |
| Production Capacity | 2400-3000 Metric tons monthly. | | | | |
| Brand Name | HENTEC | | | | |
| Certificatesand Standard | 1) ISO9001-2008/ISO 9001:2008; 2) CQM CERTIFICATES; 3) SGS, CE, BV, JIS, AS, NZS, QUALICOAT, QUOLANOD AVAILABLE. | | | | |
| Guarantee | Surface color can be stable for 10-20 years indoor using. | | | | |
| | Inside: pack with plastic protective film to protect each piece. | | | | |
| Packing Details | Outside: wrap to bundle by waterproof craft paper or EPE film, or customized | | | | |
| Delivery time | Die developing and sample testing: 12-18 days . | | | | |
| , | Mass production: 25-30 days after confirming sample by buyer. | | | | |
| FOB Port | Shanghai Port | | | | |
| Payment Terms | T/T 30% for deposit, balance before delivery. | | | | |
| | | | | | |

Applications:

Our aluminum profile has a wide range of application, like Radiator, Assembly line, Frame system, Machine Guards, Stairs & Platforms, Display rack, Automotive, Motor aluminium housing, Bridge system, Vessel, Elevator, etc.

Specifications:

1.Primary Technical Data

1)Chemical composition

| Alloy | Si | Fe | Cu | Mn | Mg | Cr | Zn | Ti | Impurity | Al |
|-------|---------|---------|----------|------|----------|-----------|------|------|----------|------|
| 6063 | 0.2-0.6 | 0.35 | 0.1 | 0.1 | 0.45-0.9 | 0.1 | 0.1 | 0.1 | 0.15 | Rest |
| 6061 | 0.4-0.8 | 0.7 | 0.15-0.4 | 0.15 | 0.8-1.2 | 0.04-0.35 | 0.25 | 0.15 | 0.15 | Rest |
| 6060 | 0.3-0.6 | 0.1-0.3 | 0.1 | 0.1 | 0.35-0.6 | - | 0.15 | 0.1 | 0.15 | Rest |
| 6005 | 0.6-0.9 | 0.35 | 0.1 | 0.1 | 0.40-0.6 | 0.1 | 0.1 | 0.1 | 0.15 | Rest |

2)Mechanical property

| Alloy | I I amnar | Tensile strength | Yield strength | Elongation |
|-------|-----------|---------------------|----------------|------------|
| 6063 | T5 | ≥ 160Mpa | ≥ 110Mpa | ≥ 8% |
| | T6 | ≥ 205Mpa | ≥ 180Mpa | ≥ 8% |
| 6061 | T6 | ≥ 265Mpa | ≥ 245Mpa | ≥ 8% |

| 公司图号 | NH | 线密度 kg/m |
|--------|--|-------------|
| HT-745 | 10.2 | 1.292 |
| HT-746 | 30 | 0.786 |
| HT-747 | 50 | 2.524 |
| HT-749 | 20 20 20 20 20 20 20 20 20 20 20 20 20 2 | 0.464 |
| HT-750 | 7.2 40 6.2 | 0.808 |
| HT-751 | 60 8.2 10.4 | 1.616 |

| 公司图号 | # 16 | 线密度 kg/m |
|--------|--|-------------|
| HT-752 | 40 | 1.646 |
| HT-753 | 80 8.2 10.2 | 2.952 |
| HT-754 | 45 27 27 27 38.2 | 2.015 |
| HT-767 | 25 25 25 25 25 25 25 25 25 25 25 25 25 2 | 1.522 |
| | | |
| | | |

Competitive Advantage:

- 1)Engineering design and support.
 2)Aluminum profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
 3)High Quality system, strictly inspection during production and whole inspection before package.
 4)Good performance, product warranty for 15 years.



Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421