Anodized Aluminum U Channel Extrusions / aluminium frame profiles

Basic Information

China . Place of Origin: НТ . Brand Name: CA,CE Certification: Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Aluminum Extrusion Channel

• Alloy: 6063,6061,6005 • Material: Aluminum

Suface Treatment: Mill Finished, Anodized, etc

T4, T5, T6, T66 • Temper:

Application: Buildings,commercial,industrial • Highlight: construction aluminium profile, aluminium profile extrusion

Product Description

Anodized Aluminum U Channel Extrusions / aluminium frame profiles

- 1. Alloy:6063,6061,6005 or according to customer's choice
- 2. Material:Aluminum
- 3. Suface Treatment: Mill Finished, Anodized , Electrophoretic coated, Powder spray coated, Fluorocarbon powder spray coated /PVDF Paint, Drawbench, Steel polished, Wood grain coated /Wooden transfer .
- 4. Deep process: Milling, Drilling, Bending, Cutting.
- Application

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

- 6. Color:clear, satin, bronze, black, golden, silver, other multicolor
- 7. Temper: T4, T5, T6, T66

Description:

| Aluminum Extrusion Channel | | | | | |
|--|--|--|--|--|--|
| Alloy 6063, 6061 or according to customer's choice | | | | | |
| T3, T4, T5, T6 | | | | | |
| Anodize (clear, satin, bronze, black, golden, silver, other multicolor), | | | | | |
| electrophoresis, powder coating, PVDF coating, wood grain painting, etc. | | | | | |
| 1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container. | | | | | |
| Industry Aluminum profile used in cars, trains machinery ,trailers ,electronics, | | | | | |
| medical and other industrial filed . | | | | | |
| ining 1. milling; 2. Drilling; 3. Bending; 4. Cutting | | | | | |
| 1. Using our moulds, free; 2. Using customer's drawing, opening mould fee | | | | | |
| need to be paid . | | | | | |
| ISO14001:2004, ISO9001:2000 | | | | | |
| Shanghai, etc. | | | | | |
| | | | | | |

Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

Specifications:

1. Primary Technical Data


1) Chemical composition

| Alloy | Si | Fe | Cu | Mn | Mg | Cr | Zn | Ti | Impurity | Al |
|-------|---------|---------|----------|------|----------|-----------|------|------|----------|------|
| 6063 | 0.2-0.6 | 0.35 | 0.1 | 0.1 | 0.45-0.9 | 0.1 | 0.1 | 0.1 | 0.15 | Rest |
| 6061 | 0.4-0.8 | 0.7 | 0.15-0.4 | 0.15 | 0.8-1.2 | 0.04-0.35 | 0.25 | 0.15 | 0.15 | Rest |
| 6060 | 0.3-0.6 | 0.1-0.3 | 0.1 | 0.1 | 0.35-0.6 | - | 0.15 | 0.1 | 0.15 | Rest |
| 6005 | 0.6-0.9 | 0.35 | 0.1 | 0.1 | 0.40-0.6 | 0.1 | 0.1 | 0.1 | 0.15 | Rest |

2) Mechanical property

| Alloy | Temper | Tensile strength | Yield strength | Elongation |
|-------|--------|------------------|----------------|------------|
| 6063 | T5 | ≥ 160Mpa | ≥ 110Mpa | ≥ 8% |
| 0003 | T6 | ≥ 205Mpa | ≥ 180Mpa | ≥ 8% |
| 6061 | T6 | ≥ 265Mpa | ≥ 245Mpa | ≥ 8% |

2. Specifications:



| NAME | A(mm) | B(mm) | T(mm) | EST.WEIGHT(kg/m | |
|--------|-------|-------|-------|-----------------|--|
| L0361 | 5.5 | 12.1 | 1.1 | 0.088 | |
| L0339 | 8.1 | 20 | 1.1 | 0.137 | |
| L0303 | 10 | 10 | 1 | 0.076 | |
| L0384 | 11.5 | 15 | 1.5 | 0.157 | |
| L0302 | 12 | 12 | 1 | 0.092 | |
| L0340 | 12.5 | 28 | 1 | 0.181 | |
| L0323 | 12.7 | 12.7 | 1 | 0.108 | |
| L0338 | 12.7 | 12.7 | 1.14 | 0.111 | |
| L0324 | 12.7 | 16 | 1 | 0.128 | |
| L0373 | 13 | 12.8 | 2 | 0.197 | |
| L0383 | 13.5 | 20 | 1.5 | 0.206 | |
| L03102 | 14 | 8 | 1 | 0.076 | |
| L0365 | 15 | 15 | 2 | 0.223 | |
| L0360 | 16 | 20 | 1.5 | 0.226 | |
| L0344 | 17 | 13 | 1.2 | 0.138 | |
| L0387 | 18.4 | 40 | 3 | 0.789 | |
| L0399 | 19.6 | 25 | 1.8 | 0.322 | |
| L0307 | 20 | 12 | 1 | 0.114 | |
| L0316 | 20 | 23 | 1.5 | 0.264 | |
| L0326 | 24.4 | 40 | 3 | 0.839 | |
| L0310 | 25 | 18 | 0.9 | 0.144 | |
| L0336 | 29 | 26 | 3 | 0.640 | |
| L0321 | 29.4 | 40 | 3 | 0.840 | |
| L03100 | 30 | 15 | 1.5 | 0.232 | |
| L0318 | 30 | 20 | 3 | 0.536 | |
| L0363 | 30 | 30.5 | 3 | 0.688 | |
| L0325 | 31 | 25 | 1.2 | 0.277 | |
| L0317 | 32 | 25 | 3 | 0.637 | |
| L0379 | 34 | 20 | 2 | 0.378 | |
| L0359 | 35.1 | 20 | 1.3 | 0.268 | |
| L0306 | 38 | 13 | 1.2 | 0.200 | |
| 10315 | 43 | 22 | 1 | 0.241 | |
| L0327 | 43.8 | 46.9 | 1.4 | 0.537 | |
| L0390 | 45 | 18 | 1.5 | 0.317 | |
| L0381 | 46 | 30 | 3 | 0.810 | |
| L0314 | 48 | 13 | 1 | 0.204 | |
| L0329 | 50 | 9.5 | 2 | 0.352 | |
| L0333 | 50 | 13 | 1.2 | 0.251 | |
| L0370 | 50 | 20 | 2 | 0.489 | |
| L0320 | 50 | 25 | 3 | 0.790 | |
| L0378 | 50 | 35 | 3 | 0.634 | |

Competitive Advantage:

- 1) Engineering design and support.
- 2) Aluminium profiles deeply processing:cutting,punching,drilling,milling,and fabricating.3) High Quality system, strictly inspection during production and whole inspection before package.





⇒HENTEC Hentec Industry Co.,Ltd

+86-13861643436

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421