



## 6063 - T5 Construction Aluminum Profile Extrusion Channel With PVDF / Powder Coating

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



### Product Specification

- Product Name: Aluminum Extrusion Channel
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Mill Finished,Anodized etc
- Temper: T4, T5, T6 ,T66
- Application: Buildings,commercial,industrial
- Highlight: **construction aluminium profile, aluminium profile extrusion**

for more products please visit us on [aluminumextrusion-profiles.com](http://aluminumextrusion-profiles.com)

## Product Description

### [Aluminum channel square aluminum tube.pdf](#)

#### 6063 - T5 Aluminum Extrusion Channel With PVDF / Powder Coating

1. Alloy :6063,6061,6005 or according to customer' s choice
2. Material:Aluminum
3. Surface Treatment: Fluorocarbon powder spray coated /PVDF Paint, Drawbench,Steel polished
4. Deep process: Milling, Drilling, Bending,Cutting.
5. Application: Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed .

#### Description:

|              |  |
|--------------|--|
| Item         | Aluminum Extrusion Channel   |
| Material     | Alloy 6063, 6061 or according to customer' s choice  |
| Temper       | T3, T4, T5, T6   |
| Surface      | Anodize (clear, satin, bronze, black, golden, silver, other multicolor) , electrophoresis, powder coating, PVDF coating, wood grain painting, etc. |
| MOQ          | 1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.   |
| Profile type | Industry Aluminum profile used in cars, trains machinery ,trailers ,electronics, medical and other industrial filed .                              |
| Machining    | 1. Milling; 2. Drilling; 3. Bending; 4. Cutting ...  |
| Moulding     | 1. Using our moulds, free; 2. Using customer' s drawing, opening mould fee need to be paid .   |
| Certificate  | ISO14001:2004, ISO9001:2000  |
| FOB Port     | Shanghai, etc.   |

#### Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

#### Specifications:

##### 1. Primary Technical Data


###### 1) Chemical composition

| Alloy | Si      | Fe      | Cu       | Mn   | Mg       | Cr        | Zn   | Ti   | Impurity | Al   |
|-------|---------|---------|----------|------|----------|-----------|------|------|----------|------|
| 6063  | 0.2-0.6 | 0.35    | 0.1      | 0.1  | 0.45-0.9 | 0.1       | 0.1  | 0.1  | 0.15     | Rest |
| 6061  | 0.4-0.8 | 0.7     | 0.15-0.4 | 0.15 | 0.8-1.2  | 0.04-0.35 | 0.25 | 0.15 | 0.15     | Rest |
| 6060  | 0.3-0.6 | 0.1-0.3 | 0.1      | 0.1  | 0.35-0.6 | -         | 0.15 | 0.1  | 0.15     | Rest |
| 6005  | 0.6-0.9 | 0.35    | 0.1      | 0.1  | 0.40-0.6 | 0.1       | 0.1  | 0.1  | 0.15     | Rest |

###### 2) Mechanical property

| Alloy | Temper | Tensile strength | Yield strength | Elongation |
|-------|--------|------------------|----------------|------------|
| 6063  | T5     | ≥ 160Mpa         | ≥ 110Mpa       | ≥ 8%       |
|       | T6     | ≥ 205Mpa         | ≥ 180Mpa       | ≥ 8%       |
| 6061  | T6     | ≥ 265Mpa         | ≥ 245Mpa       | ≥ 8%       |

##### 2. Specifications:



| NAME   | A(mm) | B(mm) | T(mm) | EST.WEIGHT(kg/m) |
|--------|-------|-------|-------|------------------|
| L0361  | 5.5   | 12.1  | 1.1   | 0.088            |
| L0339  | 8.1   | 20    | 1.1   | 0.137            |
| L0303  | 10    | 10    | 1     | 0.076            |
| L0384  | 11.5  | 15    | 1.5   | 0.157            |
| L0302  | 12    | 12    | 1     | 0.092            |
| L0340  | 12.5  | 28    | 1     | 0.181            |
| L0323  | 12.7  | 12.7  | 1     | 0.108            |
| L0338  | 12.7  | 12.7  | 1.14  | 0.111            |
| L0324  | 12.7  | 16    | 1     | 0.128            |
| L0373  | 13    | 12.8  | 2     | 0.197            |
| L0383  | 13.5  | 20    | 1.5   | 0.206            |
| L03102 | 14    | 8     | 1     | 0.076            |
| L0365  | 15    | 15    | 2     | 0.223            |
| L0360  | 16    | 20    | 1.5   | 0.226            |
| L0344  | 17    | 13    | 1.2   | 0.138            |
| L0387  | 18.4  | 40    | 3     | 0.789            |
| L0399  | 19.6  | 25    | 1.8   | 0.322            |
| L0307  | 20    | 12    | 1     | 0.114            |
| L0316  | 20    | 23    | 1.5   | 0.264            |
| L0326  | 24.4  | 40    | 3     | 0.839            |
| L0310  | 25    | 18    | 0.9   | 0.144            |
| L0336  | 29    | 26    | 3     | 0.640            |
| L0321  | 29.4  | 40    | 3     | 0.840            |
| L03100 | 30    | 15    | 1.5   | 0.232            |
| L0318  | 30    | 20    | 3     | 0.536            |
| L0363  | 30    | 30.5  | 3     | 0.688            |
| L0325  | 31    | 25    | 1.2   | 0.277            |
| L0317  | 32    | 25    | 3     | 0.637            |
| L0379  | 34    | 20    | 2     | 0.378            |
| L0359  | 35.1  | 20    | 1.3   | 0.268            |
| L0306  | 38    | 13    | 1.2   | 0.200            |
| L0315  | 43    | 22    | 1     | 0.241            |
| L0327  | 43.8  | 46.9  | 1.4   | 0.537            |
| L0390  | 45    | 18    | 1.5   | 0.317            |
| L0381  | 46    | 30    | 3     | 0.810            |
| L0314  | 48    | 13    | 1     | 0.204            |
| L0329  | 50    | 9.5   | 2     | 0.352            |
| L0333  | 50    | 13    | 1.2   | 0.251            |
| L0370  | 50    | 20    | 2     | 0.489            |
| L0320  | 50    | 25    | 3     | 0.790            |
| L0378  | 50    | 35    | 3     | 0.634            |

#### Competitive Advantage:

- 1) Engineering design and support.
- 2) Aluminium profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
- 3) High Quality system, strictly inspection during production and whole inspection before package.
- 4) Good performance, product warranty for 15 years.

#### Description:

|              |  |
|--------------|--|
| Item         | Aluminum Extrusion Channel   |
| Material     | Alloy 6063, 6061 or according to customer' s choice  |
| Temper       | T3, T4, T5, T6   |
| Surface      | Anodize (clear, satin, bronze, black, golden, silver, other multicolor) , electrophoresis, powder coating, PVDF coating, wood grain painting, etc. |
| MOQ          | 1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.   |
| Profile type | Industry Aluminum profile used in cars, trains machinery ,trailers ,electronics, medical and other industrial filed .                              |
| Machining    | 1. Milling; 2. Drilling; 3. Bending; 4. Cutting ...  |
| Moulding     | 1. Using our moulds, free; 2. Using customer' s drawing, opening mould fee need to be paid .   |
| Certificate  | ISO14001:2004, ISO9001:2000  |
| FOB Port     | Shanghai, etc.   |

#### Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

#### Specifications:

##### 1. Primary Technical Data

###### 1) Chemical composition

| Alloy | Si      | Fe      | Cu       | Mn   | Mg       | Cr        | Zn   | Ti   | Impurity | Al   |
|-------|---------|---------|----------|------|----------|-----------|------|------|----------|------|
| 6063  | 0.2-0.6 | 0.35    | 0.1      | 0.1  | 0.45-0.9 | 0.1       | 0.1  | 0.1  | 0.15     | Rest |
| 6061  | 0.4-0.8 | 0.7     | 0.15-0.4 | 0.15 | 0.8-1.2  | 0.04-0.35 | 0.25 | 0.15 | 0.15     | Rest |
| 6060  | 0.3-0.6 | 0.1-0.3 | 0.1      | 0.1  | 0.35-0.6 | -         | 0.15 | 0.1  | 0.15     | Rest |
| 6005  | 0.6-0.9 | 0.35    | 0.1      | 0.1  | 0.40-0.6 | 0.1       | 0.1  | 0.1  | 0.15     | Rest |

2) Mechanical property

| Alloy | Temper | Tensile strength | Yield strength | Elongation |
|-------|--------|------------------|----------------|------------|
| 6063  | T5     | ≥ 160Mpa         | ≥ 110Mpa       | ≥ 8%       |
|       | T6     | ≥ 205Mpa         | ≥ 180Mpa       | ≥ 8%       |
| 6061  | T6     | ≥ 265Mpa         | ≥ 245Mpa       | ≥ 8        |

**Competitive Advantage:**

- 1) Engineering design and support.
- 2) Aluminium profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
- 3) High Quality system, strictly inspection during production and whole inspection before package.
- 4) Good performance, product warranty for 15 years.



 **HENTEC** Hentec Industry Co.,Ltd

 +86-13861643436

 aluminum@hentec.com.cn

 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421