

Custom Powder Coating Construction Aluminum Profile Aluminium Window Frames

Basic Information

- Place of Origin:
- Brand Name:
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet

China

HT

- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



Product Specification

- Product Name:
- Alloy:Material:
- 6063,6061,6005

Aluminum Extrusion Corner

Mill Finished, Anodized, etc

Aluminum

- Suface Treatment:
- Temper:Application:

• Highlight:

- T4, T5, T6 ,T66 Buildings,commercial,industrial
- construction aluminium profile, aluminium profile extrusion

Customized powder coating aluminum window frames / Aluminum angle Extrusion

- 1. Alloy :6063,6061,6005 or according to customer's choice
- 2. Material:Aluminum
- 3. Temper: T4, T5, T6, T66
- 4. Suface Treatment: Mill Finished, Anodized

Description:

| Item | Mill finished Aluminum Corner with CNC machining | | | | |
|--------------|---|--|--|--|--|
| Material | Alloy 6063, 6061 or according to customer's choice | | | | |
| Temper | T3, T4, T5, T6 | | | | |
| Surface | Anodize (clear, satin, bronze, black, golden, silver, other multicolor) , electrophoresis, powder coating, PVDF coating, wood grain painting, etc. | | | | |
| MOQ | 1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container. | | | | |
| Profile type | Industry Aluminum profile used in cars, trains machinery ,trailers ,electronics, medical and other industrial filed . | | | | |
| Machining | 1. milling; 2. Drilling; 3. Bending; 4. Cutting | | | | |
| Moulding | 1. Using our moulds, free; 2. Using customer's drawing, opening mould fee need to be paid. | | | | |
| Certificate | ISO14001:2004, ISO9001:2000 | | | | |
| FOB Port | Shanghai, etc. | | | | |

Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

Specifications:

1. Primary Technical Data


1) Chemical composition

| Alloy | Si | Fe | Cu | Mn | Mg | Cr | Zn | Ti | Impurity | Al |
|-------|---------|---------|----------|------|----------|-----------|------|------|----------|------|
| 6063 | 0.2-0.6 | 0.35 | 0.1 | 0.1 | 0.45-0.9 | 0.1 | 0.1 | 0.1 | 0.15 | Rest |
| 6061 | 0.4-0.8 | 0.7 | 0.15-0.4 | 0.15 | 0.8-1.2 | 0.04-0.35 | 0.25 | 0.15 | 0.15 | Rest |
| 6060 | 0.3-0.6 | 0.1-0.3 | 0.1 | 0.1 | 0.35-0.6 | - | 0.15 | 0.1 | 0.15 | Rest |
| 6005 | 0.6-0.9 | 0.35 | 0.1 | 0.1 | 0.40-0.6 | 0.1 | 0.1 | 0.1 | 0.15 | Rest |

2) Mechanical property

| Alloy | Temper | Tensile strength | Yield strength | Elongation |
|-------|--------|------------------|----------------|------------|
| 6063 | Т5 | ≥ 160Mpa | ≥ 110Mpa | ≥8% |
| 0000 | Т6 | ≥ 205Mpa | ≥ 180Mpa | ≥8% |
| 6061 | Т6 | ≥ 265Mpa | ≥ 245Mpa | ≥8% |

2. Specifications:



| NAME | A(mm) | B(mm) | T(mm) | EST.WEIGHT(kg/m) |
|--------|-------|-------|-------|------------------|
| L0289 | 12 | 12 | 1 | 0.063 |
| L0205 | 14 | 14 | 2 | 0.140 |
| L0290 | 15 | 15 | 1 | 0.079 |
| L0299 | 15 | 15 | 1.5 | 0.121 |
| L0261 | 15 | 15 | 2 | 0.163 |
| L02164 | 17 | 7 | 2 | 0.119 |
| L0232 | 18 | 14 | 2 | 0.170 |
| L0231 | 18 | 15 | 1 | 0.091 |
| L0291 | 19 | 19 | 1 | 0.101 |
| L0220 | 20 | 10 | 2 | 0.152 |
| L0233 | 20 | 14 | 2 | 0.181 |
| L0206 | 20 | 16 | 2.2 | 0.201 |
| L02104 | 20 | 20 | 1.3 | 0.144 |
| L0211 | 20 | 20 | 2 | 0.206 |
| L0201 | 20 | 20 | 2.5 | 0.254 |
| L0256 | 20 | 20 | 3 | 0.310 |
| L02159 | 25 | 10 | 1.2 | 0.110 |
| L0254 | 25 | 14 | 3 | 0.293 |
| L0210 | 25 | 20 | 2 | 0.233 |
| L0210D | 25 | 20 | 2.5 | 0.304 |
| L0292 | 25 | 25 | 1.2 | 0.159 |
| L02111 | 25 | 25 | 1.3 | 0.180 |
| L02105 | 25 | 25 | 1.5 | 0.207 |
| L0259 | 25 | 25 | 2 | 0.262 |
| L0214 | 25 | 25 | 3 | 0.394 |
| G405 | 25.9 | 25.9 | 1.4 | 0.190 |
| L0222 | 26 | 13 | 1.8 | 0.181 |
| L0221N | 28 | 20 | 2.5 | 0.325 |
| L0241 | 30 | 20 | 2 | 0.273 |
| L0204 | 30 | 20 | 3 | 0.382 |
| L0207 | 30 | 22 | 1.2 | 0.165 |
| L0218 | 30 | 25 | 4 | 0.553 |
| L02153 | 30 | 30 | 1.5 | 0.238 |
| L0257 | 30 | 30 | 3 | 0.470 |
| L0225 | 30 | 30 | 4 | 0.607 |
| L0227 | 30 | 30 | 5 | 0.745 |
| L0275 | 32 | 25 | 2 | 0.298 |
| L02161 | 32 | 32 | 2 | 0.336 |
| L0280 | 34 | 18 | 2 | 0.283 |
| L0281 | 34 | 25 | 2 | 0.323 |
| L0267 | 35 | 35 | 5 | 0.881 |

Competitive Advantage:

Engineering design and support.
Aluminium profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
High Quality system, strictly inspection during production and whole inspection before package.
Good performance, product warranty for 15 years.

