Anodized 6063 T3 Aluminum Door Extrusions For Home decoration

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Model Number: HD50
- Application: buildings,commercial,industrial
- Temper: T4, T5, T6 ,T66
- Suface Treatment: Mill Finished,Anodized etc
- Material: Aluminum
- Alloy: 6063,6061,6005
- Product Name: Aluminum Curtain Wall Profile



Product Specification

- Highlight: **aluminum door frames**, **aluminum extrusion profiles**



More Images





for more products please visit us on aluminumextrusion-profiles.com

Our Produc

Product Description

Anodized 6063 T3 Aluminum Door Extrusions For Home decoration

1. Alloy :6063,6061,6005 or according to customer' s choice
2. Material:Aluminum
3. Suface Treatment: Mill Finished,Anodized ,Electrophoretic coated,Powder spray coated,Fluorocarbon powder spray coated /PVDF Paint, Drawbench,Steel polished,Wood grain coated /Wooden transfer .
4. Deep process: Milling, Drilling, Bending,Cutting.
5. Application:
Used in casement doors and windows for living room, dinner room, bathroom, office room, meeting room, restaurant, hotel, etc.

t Introduction
for more products please visit us on aluminumextrusion-profiles.com

6. Color:clear, satin, bronze, black, golden, silver, other multicolor
7. Temper: T4, T5, T6 ,T66

Description

The surface treatment :
1) Mill Finished
2) Anodized : Silver ,champagne ,light bronze ,dark bronze, black, light titanium, dark titanium. Usually the thickness of the film is 10 um.
3) Electrophoretic coated : Silver , champagne ,bronze ,black ,light bronze ,dark bronze .
4) Powder spray coated :Normal color ,special color. Thickness : 60 to 80 um .
5) Fluorocarbon powder spray coated /PVDF Paint : Normal color ,special color .
6) Drawbench
7) Steel polished
8) Wood grain coated /Wooden transfer : Imported paper, domestic paper .

Technical requirements

1) Standard: GB/75237-2004, Q/320281/PDWD-2008
2) Certification: ISO9001
3) OEM service offered
4) Material: Alloy 6063, 6061 or according to customer' s choice
Temper: T3, T4, T5, T6
5) Fabrication : 1. Milling; 2. Drilling; 3. Bending; 4. Cutting...
6) Window Accessories: Using ECO friendly EPDM leather strap that would not age for a long time with a long service life.
7) MOQ : 1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.
8) FOB Port: Shanghai Port

Applications:

Used in casement doors and windows for living room, dinner room, bathroom, office room, meeting room, restaurant, hotel, etc.

Specifications:

1.Primary Technical Data
1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

2.Specifications :



Competitive Advantage:

1)Engineering design and support.
2)Aluminium profiles deeply processing:cutting,punching, drilling, milling, and fabricating.
3)High Quality system, strictly inspection during production and whole inspection before package.

4)Good performance, product warranty for 15 years.

HENTEC Hentec Industry Co.,Ltd

+86-13861643436 aluminum@hentec.com.cn aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421