

## Powder Spray Coated Aluminum Solar Panel Frame 50 × 35mm Solar Panel **Aluminium Frame**

C	
2	
5	
	1
٦	r
-	2
-	÷
5	2
C	5
-	
5	-
	<u>ר</u>
1	٦
-	
-	3
	-
-	3
C	2
2	5
2	4
C	
C	1
2	2
-	-
	╡

Product Introduction		
for more products please visit us on aluminumextrusion-profiles.com		

Place of Origin:	China
Brand Name:	HT
Certification:	CA ,CE
• Minimum Order Quantity:	1 ton

<ul> <li>Minimum Order Quantity:</li> </ul>	1 ton
Packaging Details:	Packed with EP ,Carton ,Pallet or wooden case
<ul> <li>Delivery Time:</li> </ul>	20days
<ul> <li>Payment Terms:</li> </ul>	T/T ,L/C
<ul> <li>Supply Ability:</li> </ul>	3000tons each month



**Basic Information** 

• Highlight:

anodized aluminum frame, solar panel aluminum frame



## More Images



## **Product Description**

Powder Spray Coated Aluminum Solar Panel Frame 50 x 35mm Solar Panel Aluminium Frame

#### Aluminum Solar Panel Frame

Material:Aluminum Alloy :6063,6061,6060,6005 Temper: T3, T4, T5, T6 Deep process: Milling, Drilling, Bending, Cutting

#### Aluminum Extrusion Solar Panel Frame

Aluminum solar frame is widely used as the frame of solar panel, and then it is also called as aluminum solar panel frame. Our aluminum solar frames adopt L connector or screw joint, resulting in well fixed structure with durability. They are of high quality and at low price.

#### Features:

- 1) 30\*25 suitable for 30-120W solar modules
- 2) 35\*35 suitable for 80-180W solar modules
- 3) 50\*35 suitable for 160-220W solar modules
- 4) Many other custom made sizes available, such as: 45\*35mm, 60\*35mm, 46\*40mm, 46\*50mm, etc.

### Specifications :

Item	Aluminum Extrusion Solar Panel Frame
Material	Alloy 6063, 6061 or according to customer's choice
Temper	T3, T4, T5, T6
Surface	Anodize (clear, satin, bronze, black, golden, silver, other multicolor) , electrophoresis, powder coating, PVDF coating, wood grain painting, etc.
Color	Any color based on Standard Germany RAL Mark
MOQ	1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.
Profile type	used as the frame of solar panel
Fabrication	1. Milling; 2. Drilling; 3. Bending; 4. Cutting.
Moulding	1. Using our moulds, free; 2. Using customer's drawing, opening mould fee need to be paid.
Mould size	25*25, 35*35,30*46, 46*50, 30*25, 40*40 ,50*35,etc.We can provide customized aluminum solar frames upon to customers' request.
FOB Port	Shanghai, etc.

1.Alloy :6063,6061,6005 or according to customer's choice

2.Material:Aluminum

3.Suface Treatment: Mill Finished, Anodized , Electrophoretic coated, Powder spray coated, Fluorocarbon powder spray coated / PVDF Paint,  $\label{eq:constraint} Drawbench, Steel \ polished, Wood \ grain \ coated \ /Wooden \ transfer \ .$ 

Deep process: Milling, Drilling, Bending,Cutting.
 Application: Aluminum solar frame is widely used as the frame of solar panel.
 Color:clear, satin, bronze, black, golden, silver, other multicolor

HD太阳能系列型材图

7.Temper: T4, T5, T6 ,T66

太阳能系列

#### 新图号 新图号 简图 线密度 kg/m 线密度 kg/m 简图 旧图号 旧图号 GT001 GT607 45.1 4.8 0.987 0.803 7 45.1 G701 G007 GT002 GT008 0.530 0.633 角码为GT00 G702 G008 35 GT003 GT009 0.615 0.494 G795 G009 8.5 11. GT004 GT010 0.466 0,496 G794 G010 11.6 GT005 GT011 0.814 0.388 G590 G011 50 11.6 GT006 GT012 0.681 0.290 G012 G591 ÷ | | \_ 40

209 线密度仅供参考,出货以实际磅重为准!

Introduction

# HD太阳能系列型材图 国家免检

新图号	444 144	线密度	新图号	44	线密度
旧图号	简图	kg/m	旧图号	简图	kg/m
GT013	RT013	0.372	GT019	00 00 00 00	0.665
G778	17		G599	35	
GT014	*	0.367	GT020	0	0.400
G594	25		G846		
GT015	5	0.183	GT021	¥	0.884
G595			Z081	60	
GT016	32	0.248	GT022	11.6 S'12	1.228
G596			Z082	50	
GT017	38	0.534	GT023	9	0.952
G597	30		Z083	67	
GT018	11.5	0.339	GT024	S75	1.073
G598			Z084	50	

线密度仅供参考,出货以实际磅重为准! 210

太阳能系列 Solar energy series HD太阳能系列型材图

新图号	Art 144	线密度	新图号		线密度
旧图号	简图	kg/m	伊图号	简图	kg/m
GT025 角码为GT026	8.5 	0.653	GT031	35	0.548
G895	38		G893	30	
GT026	40.2	0.732	GT032	7.6 SE	0.279
G896	40.2		G894		
GT027 角码为GT026		0.424	GT033	46,4	1.711
G915	28		G913	46.4	
GT028 角码为GT026	***	0.524	GT034 角码为GT033	05	0.745
G916	35		G914	35	
GT029	L L	1.300	GT035	05	0.398
G822	42		G222		
GT030 角码为GT029		0.567	GT036	11.5 05	0.754
G823	35		G224	35	

211 线密度仅供参考,出货以实际磅重为准!

		HD	<b>、阳能系列</b>	型材图	国家免
新图号	简图	线密度	新图号	简图	线索的
旧图号	[H] [2]	线密度 kg/m	旧图号	简图	线密度 kg/m
GT037	33	0.172	GT052	40.2	0.728
G229				1	
GT038	G WJ	0.374	GT054	*	0.509
G230	25		角码为 GT052	35	
GT039	99	0.626	GT055	****	0.537
G889	30		角码力GT052	35	
GT040	11.5	0.756	GT061	25	0.161
G888	50				
GT041 1时为GT026	05	0.692	GT062	201 - 201	0.340
G187	35			25	
GT042 面码为GT026	× 11-	0.443	GT063	30	0.209

线密度仅供参考,出货以实际磅重为准! 212

太阳能系列 Solar energy series HD太阳能系列型材图

新图号	简图	线密度	新图号		All she at
旧图号	181 [01	kg/m	旧图号	简图	线密度 kg/m
GT064	27 <u>2</u> <u>0</u> <u>0</u>	0.394	GT076 指码为 GT050	8	0.698
GT068		0.497	GT077A \$	11.6 2 5 60	0.848
GT069	8.5 10 25	0.613	GT078A	÷	0.635
GT070 角码为 GT050	S2 25	0.312	GT079	₽ ₽ 25	0.524
GT071		0.687	GT080	9 03 35	0.651
GT072	12.5	0.378	GT081	0 0 12	0.395

#### 213 线密度仅供参考,出货以实际磅重为准!

