


80 um Anodized 6061 Aluminum Profile , Structural Aluminium Profiles For Restaurant , Hotel

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Model Number: HD50
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft and pallet
- Delivery Time: 20days
- Payment Terms: T/T or L/C
- Supply Ability: 100 000ton each month




Product Specification

- Highlight: aluminium structural sections, structural aluminium extrusions



More Images



Product Description

80 um Anodized 6061 Aluminum Profile , Structural Aluminium Profiles For Restaurant , Hotel

Material:Aluminum
Alloy :6063,6061,6060,6005
Temper: T3, T4, T5, T6
Deep process: Milling, Drilling, Bending,Cutting

Description

The surface treatment :

- 1) Mill Finished
- 2) Anodized : Silver ,champagne ,light bronze ,dark bronze ,black ,light titanium ,dark titanium. Usually the thickness of the film is 10 um.
- 3) Electrophoretic coated : Silver , champagne ,bronze ,black ,light bronze ,dark bronze .
- 4) Powder spray coated :Normal color ,special color. Thickness : 60 to 80 um .
- 5) Fluorocarbon powder spray coated /PVDF Paint : Normal color ,special color .
- 6) Drawbench
- 7) Steel polished
- 8) Wood grain coated /Wooden transfer : Imported paper, domestic paper .

Technical requirements

- 1) Standard of our Structural Aluminium Profiles : GB/75237-2004, Q/320281/PDWD-2008
- 2) Certification: ISO9001

Our Product Introduction

to

- 3) OEM service offered
- 4) Material: Alloy 6063, 6061 or according to customer' s choice
Temper: T3, T4, T5, T6
- 5) Fabrication : 1. Milling; 2. Drilling; 3. Bending; 4. Cutting...
- 6) Window Accessories: Using ECO friendly EPDM leather strap that would not age for a long time with a long service life.
- 7) MOQ : 1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.
- 8) FOB Port: Shanghai Port

Applications:

Structural Aluminium Profiles is widely used in casement doors and windows for living room, dinner room, bathroom, office room, meeting room, restaurant, hotel, etc.

Specifications:

1.Primary Technical Data

1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

1.Alloy :6063,6061,6005 or according to customer' s choice

2.Material:Aluminum

3.Surface Treatment: Mill Finished,Anodized ,Electrophoretic coated,Powder spray coated,Fluorocarbon powder spray coated /PVDF Paint, Drawbench,Steel polished,Wood grain coated /Wooden transfer .

4.Deep process: Milling, Drilling, Bending,Cutting.


5.Application:

Used in casement doors and windows for living room, dinner room, bathroom, office room, meeting room, restaurant, hotel, etc.

6.Color:clear, satin, bronze, black, golden, silver, other multicolor



7.Temper: T4, T5, T6 ,T66

2.Specifications :



Competitive Advantage:

- 1)Engineering design and support.
- 2)Aluminium profiles deeply processing:cutting,punching, drilling, milling, and fabricating.
- 3)High Quality system, strictly inspection during production and whole inspection before package.
- 4)Good performance, product warranty for 15 years.



 **HENTEC** Hentec Industry Co.,Ltd

 +86-13861643436

 aluminum@hentec.com.cn

 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421