# **Customized Aluminium Profile System Assembly Line With 20 Years** Warranty

# **Basic Information**

. Place of Origin: China . Brand Name: Hentec

ISO14001:2004, ISO9001:2000 Certification:

Minimum Order Quantity:

 Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



# **Product Specification**

• Product Name: Aluminum Profile System

• Alloy: 6063 6061 Aluminum • Material: Suface Treatment: Anodized

• Deep Process: Milling, Drilling, Bending, Cutting

• Temper:

• Highlight: modular aluminium profile system,

aluminium extrusion frame system





## **Product Description**

#### Customized Aluminium Profile System Assembly / Assembly Line

- (1). Suitable for industry, architecture, transportation and so on.
- (2).20 years warranty.
- (3). High corrosion resistance.
- (4).5-10 years weather resistance.
- (5). Good wear resistance & anti-scratch.
- (6). Size customized

ndustrial aluminium profile
6000series aluminium alloy
T4 T5 T6
Mill finish,powder coating, anodizing, wooden grain coating,polishing,eletrophoresis,PVDF, sanding blasting, etc.
20 30 45 80 90 series
6ММ,8ММ
Customized
Normally square,round and T-shaped,or customized
Silver,black,blue,wood color,according to clients' requirements.



#### Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.



# Specifications:

## 1.Primary Technical Data

## 1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

#### 2)Mechanical property

_/							
Alloy	Temper	Tensile	Viold strongth	Elongation			
Alloy	l ember	strength	Tield Strength				
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%			
0003	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%			
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%			

			1			
公司图号	# H	线密度 kg/m		公司图号	# 16	线密度 kg/m
HT-745	40	1.292		HT-752	40	1.646
HT-746	30	0.786		HT-753	80 8.2 10.2	2.952
HT-747	277 10.2 10.2	2.524		HT-754	45 2 0 3 1 0 0 4	2.015
HT-749	207.52	0.464		HT-767	45 45 77 77 77 77	1.522
HT-750	7.2 40 6.2	0.808				
HT-751	60 8.2 10.4	1.616				

## **Competitive Advantage:**

- 1)Engineering design and support.
  2)Aluminum profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
  3)High Quality system, strictly inspection during production and whole inspection before package.
  4)Good performance, product warranty for 15 years.



# **⇒HENTEC** Hentec Industry Co.,Ltd



+86-13861643436





Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421