

Anodized Radiator Aluminium Heatsink Extrusion, Extruded Heat Sink Profiles


Basic Information

. Place of Origin: China **HENTEC** . Brand Name: CA,CE · Certification: Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Aluminum Heatsink Extrusion Profiles

• Alloy: 6063,6061,6005 • Material: Aluminum

Mill Finished, Anodized , Electrophoretic Suface Treatment:


Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

T4, T5, T6, T66 • Temper:

· Highlight: aluminium heatsink extrusion,

aluminium extrusion heat sink profiles



Product Description

Anodized Anodized Heatsinks Extrusion Profiles , Aluminum Radiator

Our Advantages:

- 1. 17+ years experience in providing ONE-STOP customized aluminium extrusion and machining solution; 11+ years of exporting to 40+ countries;
- 2. 100% new material
- 3. Competitive prices with short lead-time for both tooling and parts, because we do everything in-house
- 4. Effective and strong technical support (30+ engineers) and excellent sales services .
- 5. Sufficient production capacity (22 extrusion lines; 3+ CNC machines).
- 6. Efficient communication (48-hour quote lead time).

Quality Control: We operate the most strict quality system,the detection is from the material,production process to final product,and ensure the product quality.

Process: Die design--Die making--Smelting and alloying--Quality control--Extruding--Cutting--Heat treatment--Surface treatment--Welding--Packing

Packing: Packed with plastic film, then wrap by craft paper or EPE film.

Technology Supports

- 1. Engineering Design.
- 2. Quality Standard: China GB, according to the Drawing and the Customer's Details.

Specifications:

- 1. Primary Technical Data
- 1) Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

=/ meenamea property									
	Alloy	Temper	Tensile strength	Yield strength	Elongation				
6	6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%				
	0000	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%				
	6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%				



Competitive Advantage:
We can offer professional Manufacturing and exporting service, OEM/ODM for Metal & Plastic parts in China. All the parts manufactured by CNC Lathe & Milling Machine Center.



Tag: **LED Aluminum Heat Sink** extruded aluminum heat sink

+86-13861643436 aluminum@hentec.com.cn aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421

