Silver Anodized Industrial Aluminium Profiles Aluminium Cylinder **Shell**

Basic Information

. Place of Origin: China HENTEC . Brand Name: SGS · Certification: Minimum Order Quantity:

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Aluminum Cylinder

• Alloy: 6063,6061 • Material: Aluminium


Suface Treatment: Anodized ,Electrophoretic Coated,Powder

Spray Coated

• Deep Process: Milling, Drilling, Cutting

• Temper: T5, T6

· Highlight: aluminum extrusion profiles, aluminium extruded profiles



Product Description

Silver Anodized Industrial Profile Systems / Aluminium Cylinder Shell

Description	Aluminum/Aluminium industrial extrusion profile for cylinder pump	SGS TEST APPROVAL
L		SGS TEST
Alloy/Temper	6061 /6063 T5/T6	APPROVAL
Surface	Mill finishes;Anodized; Powder coated;Wooden grain, Machine/Acid polished and	SGS TEST
treatment	etc	APPROVAL
Standard apply	EN755;DIN;ASTMB221;GB5237-2008 and etc.	SGS TEST
		APPROVAL
Price	SMM/LME Primary aluminum price + the most competitive conversion cost	SGS TEST APPROVAL
Delivery	sample: within 20 days; order: within 20 days	SGS TEST
timetable	· ·	APPROVAL
Payment term	20% deposit, the balance pay against B/L copy within 7 days	SGS TEST APPROVAL
Packing standard	Protected film and pearl cotton inside and shrink film outside	SGS TEST APPROVAL
	I.	

Applications:

Mainly used for industrial production, such as automation equipment, enclosure of the skeleton and the companies according to their own customized mold machinery and equipment, such as assembly line conveyor, hoist, dispenser, testing equipment, shelves, etc., electronic machinery industries and clean room with a gain majority.

Competitive Advantage:

- 1. Professional production workshop for extrusion and colored profile manufacturing,including we own 4500 tons extrusion machine,automatic vertical electrophoresis production lines.
- 2. Strict quality control and inspection before goods delivery.
- 3. Production standards: GB5237-2008 or other International standards.
- 4. With 15 years experience, our factory is well recognised by clients and enjoys a good reputation among overseas markets.
- 5. Professional R&D team .



FAQ For Saving Your Precious Time!

Q1: What's the thickness for anodizing? Can you do 15um?

A: Our normal thickness is about 10 um. Yes, we can do 15um and above.

Q2: What color you can do for powder coating? The thickness for powder coat?

A: We can do any color for powder coat as long as you can provide the color sample. Our normally powder coating thickness is 60-80um.

Q3: What color you can do for wood grain?

A: Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc.If you need any other colors, we can do according to the color samples you provide.

Q4: How's the weather resistance for wood grain finish D1010?

- A: (1).Powder:Akzo Noble Interpon D1010.
- (2). Wood grain film:Italian Menphis.
- (3). Standard complied: American AAMA Standard. 2603
- (4). UV test:1000 hours.
- (5). Salt spraying test:1000 hours.
- (6). Normal weather:10 years color guarantee.

Q5: What certification do you have? What's your standard?

A: We have ISO certification. Our standard is DIN, AAMA, AS/NZS, China GB.

Q6: What's the delivery time for samples and mass production?

A: (1).2-3 weeks to make the new moulds and make free samples.

(2). 3-4 weeks after receipt of deposit and confirmation of the order.

→ HENTEC Hentec Industry Co.,Ltd



+86-13861643436



aluminum@hentec.com.cn



@ aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421