6063- T5 Silvery Black Cylinder Shell Industrial Aluminum Profile With Longlife

Basic Information

Place of Origin: China
Brand Name: HENTEC
Certification: SGS
Minimum Order Quantity: 1 ton

• Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20daysPayment Terms: T/T ,L/C

• Supply Ability: 100 000ton each month



Product Specification

Product Name: Industrial Aluminium Profile

Alloy: 6063,6061Material: Aluminum

Suface Treatment: Mill Finished, Anodized , Electrophoretic

Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

• Temper: T4, T5, T6

 Highlight: aluminum extrusion profiles, aluminium door frame HENTEC



Product Description

6063- T5 Silvery, Black Industrial Aluminium Profile / Cylinder Shell

We have a wide range of Aluminum Extrusion for Industry including:

- 1. Alloy:6060/6061/6063/6082/6005 etc T6/T5 are available;
- 2. Length <=13 meters
- 3. Surface treatment: Mill, Anodized, Powder Coated, Wooden Transfer, etc
- 4. Fabricator: cutting, milling, punch, stamping, drill, CNC, assembly, package. etc.
- 5. One-stop Service: Mould, Extrusion, Finishing, Fabricator and Assembly, Delivery.
- 6. Any OEM and design are welcome.

Description:

Item	Aluminum extruded cylinder shell with CNC machining
Material	Alloy 6063, 6061,6005,6060 or according to customer's choice
Temper	T4, T5, T6,T66
Surface	Anodize (clear, satin, bronze, black, golden, silver, other multicolor), electrophoresis, powder coating, PVDF coating, wood grain painting, etc.
MOQ	1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.
Usage	Widely used in the instruction and electronic areas
Machining	High-precision machining available upon request (lathe/milling/CNC machining/polishing/punching/drilling/taping, etc.)
Moulding	Using our moulds, free; 2. Using customer's drawing, opening mould fee need to be paid.
Certificate	ISO14001:2004, ISO9001:2000
FOB Port	Shanghai, etc.

ADVANTAGES of choosing Hentec Alu.:

- --1--. QUALITY GUARANTEED: One-stop service, tool design, smelting, extruding, machining, surface treatment, packing as well as assembling can be all finished in house.
- --2--. RELIABLE QUALITY: Our company is ISO9001: 2008 certified
- --3--. High Efficiency: Most competitive price with short lead time for tooling design and the parts
- --4--. Efficient communication (48-hour quotes price/lead time/MOQ)
- --5--. Compliant test with RoHS

Quotation is usually based on:

- 1) Detail drawings;
- 2) Buyers' samples;
- 3) Specification, pictures of the products.

Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.



Specifications:

1.Primary Technical Data

1)Chemical composition

·/onemeas composition										
Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

7 F -F								
Alloy	Temper	Tensile strength	Yield strength	Elongation				
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%				
0000	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%				
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%				

新图号 山图号	何 图	线密度 kg/m	新图号	简 图	线密度 kg/m
GQ001	Day 2	5.445	GQ937	5586 S	43.160
G674	18		G029		
GQ002	die 2	16.074	GQ038	5)155_	51.131
G675	90		G433		
GQ003	0.55.5 E	25./0	GQ039	160	51.840
G676			G169		
GQ004	(PU)	24,030	GQ010	2782 B	61.120
G179	107		G434	170	
GQ005	128	30.877	GQ011	9071	58.323
G412			G249		
GQ006	(a):40 3	33.144	GQ020	(3/8°) ×	5.650
G6//	128		G852		

新图号	简 图	线密度 kg/m	新图号	何 图	线密度
旧图サ	MI	kg/m	旧图号	阿田	线密度 kg/m
CQ021	60 USS 2	7.780	GQ354	(g) 2	3.422
G853			G673	45	
GQ022	70	11.020	GQ>+0	(8)27 SEE	30.380
C8>4			G166	153	
GQ023	88	14.520	GQ911	90	6.958
C855			G348		
GQ024	(0,72) 50 E	20.510	GQ)44	(ma) 15	9.560
G\$56	102		G362	78	
GQ025	110 00/57	24.770	GQ916	10.8 10.8	12:295
GQ052			G384		
6Q033	(62) ° 2	5.710	GQ919	20 m	17.270
G258	55		G441	120	

Competitive Advantage:

- Engineering design and support.
 Aluminium profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
 High Quality system, strictly inspection during production and whole inspection before package.
 Good performance, product warranty for 15 years.













