



6063 6061 Standard Aluminum Window Extrusion Profiles CA CE Certified

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: HENTEC,KUNTAI
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: EP Paper ,kraft and pallet
- Delivery Time: 20days
- Payment Terms: T/T or L/C
- Supply Ability: 100 000 ton each month


 **HENTEC**



Product Specification

- Product Name: Aluminum Window Extrusion Profiles
- Alloy: 6063,6061
- Material: Aluminum Alloy
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T4, T5, T6
- Highlight: **extruded aluminium profiles,
profile aluminum extrusions**

 **HENTEC**



Product Description

Powder Painted Aluminum Window Extrusion Profiles / Standard Aluminum Extrusion Profiles

Description :

- (1). Product: aluminium profile
- (2). 20 years warranty.
- (3). High corrosion resistance.
- (4). 5-10 years weather resistance.
- (5). Good wear resistance & anti-scratch.
- (6). Size customized.

More Information:

1. Material: Aluminium alloy 6063, 6061.
2. Temper: T5, T6.
3. Quality standard: DIN; AAMA; AS/NZS; CHINAGB.
4. Surface treatment: Mill finish, anodized, powder coated, wood grain, polished, brushed, electrophoresis, etc.
5. Color available: Anyone is available based on your color samples.
6. Packing details: Shrinking film; Plastic & kraft paper; Wooden pallet
Carton packing; By customer's requirements.
7. Samples Time: Normally, 2-3 weeks.
8. Delivery: 25-30 days for mass production.
9. Production Capacity: 6000MT/Month
10. MOQ: It's based on the drawings. Basically, it's 1 ton.
11. Port: Shanghai; As per requested.

Applications:

Hotel | Home | Commercial Building | Closet | Bathroom| Curtain Wall | Industry | And Others

Specifications:

1.Primary Technical Data

1) Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

Competitive Advantage:

1. 22 years' experiences of manufacturing, 12 years' exporting experiences .
2. STRONG R&D: Help customers finalize the design, strong tool design ability,excellent pressing and surface treament technology.
- 3.Strict quality management: ISO Administration system.
4. 24 hours on-line communication.Professional, Patient, Flexible.
5. High capacity of manufaturing and wide range of products.
6. Be able to provide secondary fabricating.
7. Small order isaccepted.
8. Be able to provide one-stop supply solution.
9. Multiple payment methods: TT, LC.



HENTEC Hentec Industry Co.,Ltd

+86-13861643436

aluminum@hentec.com.cn

aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421