OEM Design Aluminum Extrusions For Electronics / Aluminum Cover / Shell

Basic Information

- Place of Origin:
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 500 pcs
- Packaging Details: Ep paper ,kraft ,pallet

China

- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 80 000ton anually



Product Specification

- Product Name:
- Alloy:
- Material:
- Suface Treatment:
- Deep Process:
- Temper:
- Highlight:

Aluminum Enclosure	
6063,6061,6005	

Aluminum

- Alodine, Anodized, Electrophoretic Coated, Powder Spray Coated
- Milling, Drilling, Bending, Cutting
- T5, T6 ,T66
- extruded aluminium profiles, aluminum extrusion profiles



OEM Aluminum Extrusions For Electronics / Aluminum Cover / Shell

Product Description

Item	OEM Aluminum Extrusion Profile						
Material	6000 series Aluminium T4, T5, T6						
Size / Thickness	General profiles thickness from 0.8 to 5.0mm, length from 3m-6m or customized available; Anodized protection film thickness from 8~25 um, powder coating from 40 ~ 120 um.						
Shape	square, round, T shaped, rectangular, customized						
Surface treatment	mill finish, anodized, powder coating, wood grain, sandblasting, and so or						
Colors	silver, black, blue, wood color, RAL powder coating color and so on						
MOQ	500kgs for each item						
FOB Port	Shanghai						
payment terms	T/T 30% for deposit, balance before shipping.						
settlement term	Charge by final actual weight or by drawing theoretical weight.						
Certificate and Standard	SGS, CE available						

Warranty

- 1. GB5237-2008 equal to EN12020-1.2(2001);
- 2. GB6892-2006 equal to DIN 1725
- 3. Within 15 years without color changing, all life without surface peeling off;

Moulding

we open the new die within 10days

Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

Specifications:

1. Primary Technical Data

1) Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation	
6063	T5	≥ 160Mpa	≥ 110Mpa	≥8%	
0000	Т6	≥ 205Mpa	≥ 180Mpa	≥8%	
6061	Т6	≥ 265Mpa	≥ 245Mpa	≥8%	

2. Specifications:

Excellent material for smooth and subtle edges. Elegant appearance. Surface treatment: colorful anodized ,powder coated , electrostatic ,PVDF . Suitable for constructions and other industrial purposes. Customized surface finishes are welcome.

Competitive Advantage:

1) Engineering design and support.

- 2) Aluminum profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
- 3) High Quality system, strictly inspection during production and whole inspection before package.4) Good performance, product warranty for 15 years.



HENTEC Hentec Industry Co.,Ltd

+86-13861643436

aluminum@hentec.com.cn

@ aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421