Anodized Extruded Aluminium Frame For Solar Panel, Aluminum Profile

Basic Information

. Place of Origin: China HENTEC . Brand Name: CA,CE · Certification: Minimum Order Quantity:

• Packaging Details: Packed with EP ,Carton ,Pallet or wooden

Delivery Time: 20days T/T ,L/C • Payment Terms:

Supply Ability: 3000tons each month



Product Specification

• Product Name: Aluminum Solar Panel Frame

• Alloy: 6063,6061,6005 • Material: Aluminum

Suface Treatment: Anodized ,Electrophoretic Coated,Powder

Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

T5, T6 Temper:

· Highlight: aluminium solar panel frame,

solar panel aluminum frame



Product Description

Anodized Aluminum Solar Panel Frame With Screw Joint / Corner Key Joint

Hentec Industry Co.,Ltd established in 2005, and located in Wuxi Jiangsu.

As professional aluminum product supplier, we served many company and factory from different country.

We own the strong and complete supply system that could meet your any requirement of product and service.

We are good in supplying all kind of aluminum product, including aluminum profile, aluminum sheet and aluminum part.

We cooperate with many famous and powerful factory that could offer the perfect service and technical supplort.

We adhere to the principle of "Customer is the first" to serve every customer.

We are always aiming to provide customer the professional technical support, optimal rationalization advice, to save your time and cost.

We will offer you the professional one-step services with customized application solution and professional design product.

Hope we could take you the good experience of purchasing.

Description:

Aluminum Extrusion Solar Panel Frame

Aluminum solar frame is widely used as the frame of solar panel, and then it is also called as aluminum solar panel frame. Our aluminum solar frames adopt L connector or screw joint, resulting in well fixed structure with durability. They are of high quality and at low price.



We Supply The Quality Aluminum Solar Panel Frame

Features:

- 1) 30*25 suitable for 30-120W solar modules
- 2) 35*35 suitable for 80-180W solar modules
- 3) 50*35 suitable for 160-220W solar modules
- 4) Many other custom made sizes available, such as: 45*35mm, 60*35mm, 46*40mm, 46*50mm, etc.

Specifications:

Aluminium Alloy	6063,6060,6061
Temper	T4-T6
Quality Standard	GB/T 5237-2008, EN755-9,EN12020, JST,AA STANDARD.
Quality Certificate	ISO9001, ISO14001,OHSAS18001,DNV,QUALANOD, QUALICOAT
Useage	Solar profile
	Power coatinag: AKZO Noble etc.
	PVDF: 2coated, 3 coated.
Surface Treatment	Anodizing: Silver, Champagne, Bronze, Black, Gold, Imitating Steel, Titanium
Dunace meatinem	Wood grain: As per customers' samples.
	Polishing, Mechanical, Chemcial.
	Electrophoresis: Sliver, Champagne, Black, Golden, Titanium, etc.
Processing	Drilling, Bending, Aluminium profile fabrication, Precise cutting ect.
MOQ	1000 Kilogram
Packing	protection film + shrink plastic film or kraft paper.
acking	Timber packing + Metal trolly;
Payment Terms	TT 30% before production, the rest should be balanced before loading.

太阳能系列

HD太阳能系列型材图

新图号	简图	线密度	新图号	Adv. trat	线架度
旧图号	间 国	线密度 kg/m	旧图号	简图	线密度 kg/m
GT001	45.1	0.987	GT607	08	0.803
G701	45.1		G007	30	
GT002 育码为GT001	24	0.530	GT008	0 0	0.633
G702	35		G008	25	
GT003	\$5	0.615	GT009	*	0.494
G795	25		G009	25	
GT004	8.5	0.466	GT010	11.5	0.496
G794	16		G010		
GT005	94	0.814	GT011	9	0.388
G590	50		G011		
GT006	11.6	0.681	GT012	238	0.290
G591	40		G012	,	

209 线密度仅供参考,出货以实际磅重为准!

HD太阳能系列型材图 国家免检

新图号	简图	60 (85 IB)	新图号	简 图	40 s81 m²
旧图号	Jel 131	线密度 kg/m	早图田	简 图	线密度 kg/m
GT013	9	0.372	GT019	09 211.5	0.665
G778	17		G599	35	
GT014		0.367	GT020	12	0.400
G594	25		G846		
GT015	7	0.183	GT021	9	0.884
G595			Z081	60	
GT016	32	0.248	GT022	11.6	1.228
G596	<u>.</u>		Z082	50	
GT017	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0.534	GT023	94	0.952
G597	30		Z083	67	
GT018	11.5	0.339	GT024	\$25	1.073
G598			Z084	50	

线密度仅供参考,出货以实际磅重为准! 210

太阳能系列 Solar energy saries

HD太阳能系列型材图

新图号	简图	线密度	新图号	简图	40 star star
旧图号	(0.57 300)	线密度 kg/m	旧图号	简图	线密度 kg/m
GT025 角码为GT026	8.5	0.653	GT031	7.6	0.548
G895	38		G893	30	
GT026	40.2	0.732	GT032	7.6	0.279
G896	40.2		G894		
GT027 舶码为GT026	8.5	0.424	GT033	46.4	1.711
G915	28		G913	46.4	
GT028 年码为GT026	8.5	0.524	GT034 角码为GT033	92	0.745
G916	35		G914	35	
GT029	42	1.300	GT035	11.5	0.398
G822	42		G222		
GT030 物码为GT029	35	0.567	GT036	11.5	0.754
G823	35		G224	35	

211 线密度仅供参考,出货以实际磅重为准!


新图号	简图	线索度	新图号	Ark: test	(4) (秦) (6)
旧图号	Ind Titl	线密度 kg/m	日图号	简图	线密度 kg/m
GT037	22	0.172	GT052	40.2	0.728
G229	Ш			1	
GT038	7	0.374	GT054	*	0,509
G230	25		角程为 GT052	35	
GT039	99	0.626	GT055	38	0.537
G889	30		角形为GT052	35	
GT040	46	0.756	GT061	28	0.161
G888	50				
GT041 组码为GT026	30	0.692	GT062	25	0.340
G187	35			25	
GT042 角码为GT026	20	0.443	GT063	2	0.209
G789	35				

线密度仅供参考,出货以实际磅重为准! 212

太阳能系列 Solar energy series

HD太阳能系列型材图

新图号	简图	线密度
旧图号	间	kg/m
GT064	N 3 W	0.394
GT068	18	0.497
GT069	8.5	0.613
GT070 角码为 GT050	8 25	0.312
GT071	12.5	0.687
GT072	12.5	0.378




213 线密度仅供参考,出货以实际磅重为准!

HD太阳能系列型材图

国家免检

新图号	简图	线密度 kg/m
旧图号	1100 1100	kg/m
GT082	7.3	0.245
GT083	7.3	0.267
GT084	35	0.515
GT085	8	0.646
GT086	11.5	0,674
GT087	11.6	0.655



Applications:

Competitive Advantage:

In addition to high quality ,we at Hentec office offer customer complete service .Our aluminum solar frame comes with a 15 year warranty .Maintenance service is also available .



⇒HENTEC Hentec Industry Co.,Ltd



+86-13861643436





aluminum@hentec.com.cn @ aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421