# Pneumatic / Motor Cylinder Shell 6005 Industrial Aluminium Profile

# **Basic Information**

. Place of Origin: China HENTEC . Brand Name: SGS · Certification: Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



# **Product Specification**

• Product Name: Industrial Aluminium Profile

• Alloy: 6063,6061,6005 • Material: Aluminum

Suface Treatment: Mill Finished, Anodized , Electrophoretic

Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

T4, T5, T6, T66 • Temper:

· Highlight: 6005 industrial aluminum profile, aluminium extrusion anodising



### **Product Description**

#### Silvery, Black Industrial Aluminium Profile Pneumatic / Motor Cylinder Shel

#### Description:

- 1) Qualified aluminium alloy: 6063, 6061, 6060, 6005, 6082 ... available
- 2) Finish: Black anodization, sandblasting, Powder Coating (Besides, our factory is also capable to provide different surface treatment for our customers to choose, such as Silkscreening, Polishing, brushing, hard anodization, natural anodization, color anodization, etc.)
- 3) Machining: The faceplate includes Stamping, CNC machining and drilling. (Besides, we can provide precision processing such as bending, welding, lathing, tapping, shearing, cutting, milling, punching, etc)
- 4) OEM & ODM design is welcome.

#### Adtantages of choosing HENTEC Alu.:

- --1--. Quality Guaranteed : One-stop service, tool design, smelting, extruding, machining, surface treatment, packing as well as assembling can be all finished in house.
- --2--. Reliable Quality: Our company is ISO9001: 2008 certified
- --3--. High Efficiency: Most competitive price with short lead time for tooling design and the parts
- --4--. Efficient communication (24-hour quotes price/lead time/MOQ)
- --5--. Compliant test with RoHS

#### Quotation is usually based on:

- 1) Detail drawings;
- 2) Buyers' samples;
- 3) Specification, pictures of the products.

#### Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

#### Specifications:

#### 1.Primary Technical Data

#### 1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6				0.45-0.9					Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

#### 2)Mechanical property

	-)IVICOHAHIOAI F	поронц				
	Alloy	Temper	Tensile	Viold strongth	Elongation	
		l ember	strength	Tield Strength		
6063	6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%	
	5005	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%	
	6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%	

新图号	简 图	线密度 kg/m	新国号	育 图	线索性 kg/m
GQ001	18 2	5.445	GQ007	25th 8	43.160
G674			G029	135	
GQ002	90 3	16.074	GQ038	933	51.131
_			$\vdash$		
GQ003	81342 E	25.70	GQ039	10kl 8	51.840
G676	107		G169	160	
GQ004	(412) E	24.030	GQ010	2005 E	61.120
G179	107		G434	170	
GQ003	(9):45 SE	30.877	GQ011	ogn og	58.323
G412	128		G249	170	
GQ006	(a):40 3 <u>2</u>	33.144	GQ020	(248°) 7	5.650
G671	128		G852		
新图号	質 图	线密度 kg/m	新图号	何 图	线密度 kg/m
	(N)	线密度 kg/m		(4) (4) (4) (4) (4) (4) (4) (4) (4) (4)	线密度 kg/m
旧图サ	60		旧图号		
旧图+ CQ021	60		IR图 <del>号</del> GQXH	(s) 2	
旧图号 CQ021 G\$53	70	7.780	旧園 <del>サ</del> GQ554 G673	45	3.422
IFI回号 CQ021 C853 GQ022 C854	70	7.780	旧画サ GQ354 G673 GQ940 G166	45	3.422
IFI回号 CQ021 G\$53 GQ022 C\$54	70 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	7.780	IFI图 <del>1</del> GQ354 GG73 GQ340 G166	45	3.422
IFI回号 CQ021 C853 GQ022 C854	70	7.780	旧画サ GQ354 G673 GQ940 G166	45	3.422
旧回サ CQ021 G853 GQ022 C854 GQ023	70 SE	7.780 11.020 14.520	GQ344 GG73 GQ340 G166 GQ911 G348	45	3.422
円回号 CQ021 G853 GQ022 C854 GQ023 G856 GQ025	70 SE	7.780 11.020 14.520	GQ254 GG73 GQ240 G166 GQ241 G34\$ GQ244 G362	45 45 133 133 88	3.422
円回号 CQ021 G853 GQ022 C854 GQ023 C855 GQ024	55 55 55 55 55 55 55 55 55 55 55 55 55	7.780 11.020 14.520	旧画サ GQ354 G673 GQ040 G166 GQ041 G348 GQ044	45 45 153 153 55 62 56	3.422 30.380 6.958
円回号 CQ021 G853 GQ022 C854 GQ023 G856 GQ025	55 55 55 55 55 55 55 55 55 55 55 55 55	7.780 11.020 14.520	GQ254 GG73 GQ240 G166 GQ241 G34\$ GQ244 G362	45 45 153 153 80 153 80 153	3.422 30.380 6.958
F  回 号  CQ021  C\$53  GQ022  C\$54  GQ023  C\$55  GQ024  G\$56  GQ025  CQ052	70 603 70 603 70 603 110 604 110 605 110 605 110 605 110 605 110 605 110 605 110 110 110 110 110 110 110 1	7.780 11.020 14.520 20.510	「日間サ GQ324 G673 GQ040 G166 GQ041 G348 GQ044 G362 GQ046 G364	45 45 133 133 58 89 62 89 89	3.422 30.380 6.958 9.560

# **Competitive Advantage:**

- 1)Engineering design and support.
  2)Aluminium profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
  3)High Quality system, strictly inspection during production and whole inspection before package.
  4)Good performance, product warranty for 15 years.



# **⇒HENTEC** Hentec Industry Co.,Ltd







♦ +86-13861643436 aluminum@hentec.com.cn aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421