

Black Anodized 6063 Aluminium Extrusion Frame System T Shaped **Aluminium Profile**

Basic Information

. Place of Origin: China

. Brand Name: HENTEC / MetalPlus

CA ,CE ,ISO14001:2004, ISO9001:2000 Certification:

Minimum Order Quantity:

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Industrial Aluminium Profile

• Alloy: 6063 • Material: Aluminum

Suface Treatment: Mill Finished, Anodized Powder Spray Coated

• Deep Process: Milling, Drilling, Cutting

• Temper:

• Highlight: 6063 aluminium extrusion frame system,

black anodized aluminium extrusion frame

, 6063 t shaped aluminium profile



Product Description

Black Anodized Industrial Aluminium Profile ,T-Slot Aluminum Extrusion Profile for Assembly Line

Hentec Industry CO.,Ltd is a manufacturer specializing in industrial aluminum profile frames. It has more than17years of industry experience in the field of aluminum profiles. Here it has top technical talents, high-end sales teams, and good presales and after-sales service. Look forward to working with you.

Product Specification

roduct openinguion					
Item	Aluminum Assembly Line				
Material	Aluminium 6000 series alloy, such as 6061, 6063, 6082 etc.				
Temper	T5, T6				
Size	customized.				
Shape	Square, flat, round, hollow, oval, triangle, U-profile, L-profile, T-profile, H-profile, customized available.				
Surface Treatment	Anodizing , Powder Painting , Mill Finished				
Color	Silver, champagne, black, bronze, gold, white or customized				
Application	Window and door with thermal break strips, curtain wall, glass wall, furniture, ceiling, kitchen, LED strip, transportation rail, vehicle, motor housing, machine, tent, solar panel, industrial profile, decoration profile etc.				
Deep Process	CNC, drilling, milling, cutting, tapping, welding, bending, assembling.				
MOQ	500 kgs for each item, usually 13-15 tons for a 20GP, 25-28 tons for a 40HQ.				
OEM service	Drawing, sample or design service offer by customer.				
Production Capacity	2400-3000 Metric tons monthly.				
Brand Name	HENTEC				
Certificatesand Standard	1) ISO9001-2008/ISO 9001:2008; 2) CQM CERTIFICATES; 3) SGS, CE, BV, JIS, AS, NZS, QUALICOAT, QUOLANOD AVAILABLE.				
Guarantee	Surface color can be stable for 10-20 years indoor using.				
Packing Details	Inside: pack with EP foam				
acking Details	Outside: craft paper ,Pallet , Wooden Case				
Delivery time	Die developing and sample testing: 12-18 days .				
,	Mass production: 25-30 days after confirming sample by buyer.				
FOB Port	Shanghai Port				
Payment Terms	T/T 30% for deposit, balance before delivery.				



Factory Capacity:

Die Center

CNC cutting: 5 sets CNC lathe:2 sets

CNC machining center: 15 sets

Extrusion Lines

Extrusion lines: 22sets imported from Japan, Italy with annual capacity 400 thousands of tons.

Anodizing Lines

With 2full-automatically horizontal type and 1 vertical type.

The oxidize aluminum materials length is up to 10m, electrophoretic materials length is up to 7.5m, with an annual output of 150,000tons.

Powder coating lines

With 2powder coating lines from Italy and 4sets of guns from Switzerland

Applications:

Industry Aluminum profile used in assembly production line , electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products.



Specifications:

1.Primary Technical Data

1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

,	17			
Alloy	llamnar	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

公司图号	黄芪	线密度 kg/m	
HT-745	10.2	1.292	
HT-746	30	0.786	
HT-747	55	2.524	
HT-749	27 7 22	0.464	
HT-750	7.2 40 6.2	0.808	
HT-751	8.2 10.4	1.616	

公司图号	黄茵	线密度 kg/m
HT-752	40	1.646
HT-753	80 8.2 10.2	2.952
HT-754	45 2 0 7 3 8.2	2.015
HT-767	\$ 17.7 2.2 2.2 2.3	1.522

Competitive Advantage:

- 1)Engineering design and support.
 2)Aluminum profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
 3)High Quality system, strictly inspection during production and whole inspection before package.
 4)Good performance, product warranty for 15 years.



⇒HENTEC Hentec Industry Co.,Ltd



+86-13861643436



aluminum@hentec.com.cn



@ aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421