# Hentec Industry Co.,Ltd aluminumextrusion-profiles.com

## Elevator Standard Aluminium Extrusion Powder Painting / Anodizing En755

#### **Basic Information**

Place of Origin: China
Brand Name: MetalPlus
Certification: SGS
Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20daysPayment Terms: T/T ,L/C

• Supply Ability: 100 000ton each month



### **Product Specification**

Material: Aluminum
 Alloy: 6063 / 6061
 Temper: T5 / T6

• Surface: Anodizing / Powder Painting

Application: Elevator DoorLogo: Silk Screen

• Highlight: elevator standard aluminium extrusion,

 $powder\ painting\ standard\ aluminium\ extrusion,$ 

en755 standard aluminium extrusion



#### **Product Description**

#### Standard Aluminum Extrusion Profile For Elevator / Powder Painting / Anodizing

MetalPlus is one of the largest manufacturers of extruded aluminium profiles in China. Since its establishment in 1997, the Company is dedicated to the design and manufacturing of advanced high precision extruded aluminium profiles. Through years of effort and perseverance, MetalPlus Aluminium's product range has expanded from architectural doors, windows and curtain walls to various industrial profiles, rail transportation, automotive, electronics application, communication technology, IT and so on.

Over the years, Metal Plus Aluminium relied on an outstanding management team, well-qualified employees, modernized management model, excellent technology, scientific production process control and stringent quality control to achieve high production capability for a full range of quality products, providing customers with high precision aluminium extruded profiles within the Shortest production timeframe and becoming a strong production base of aluminium extrusion profiles in both local and international markets.

#### **Products description:**

Material	Mainly aluminum alloy 6063, 6061
Temper	T4 T5 T6 T66
Surface Treatment	Mill Finish Powder coating Anodized Electrophoresis Sand- blasting fluorocarbon coating Wood grain
Color	Customer required
Length	Customer required
Standard	GB
Certification	ISO9001: 2008, ISO14001: 2004
Production Capacity	100 000 tons/year
Application	For window and door/curtain wall/partition,wardrobe/handrail/ solar panel etc.
Packing	Plastic Film + Ep Paper + Wooden
Delivery	20-25 days per 40FT container After confirmation of the order
Payment terms	T/T, L/C

#### **Applications:**

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed. In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

#### Specifications:

#### 1. Primary Technical Data

#### 1) Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

#### 2) Mechanical property

	oa. p. opo. cy			
Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

#### Competitive Advantage:

- 1) Engineering design and support.
- 2) Aluminium profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
- 3) High Quality system, strictly inspection during production and whole inspection before package.
- 4) Good performance, product warranty for 15 years.



# **⇒HENTEC** Hentec Industry Co.,Ltd



+86-13861643436





Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421