6063 Anodized Cylinder Metal Extrusion Profiles , Aluminum Extrusion Sections

Basic Information

Place of Origin: China
Brand Name: MetalPlus
Certification: SGS
Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20daysPayment Terms: T/T ,L/C

• Supply Ability: 100 000ton each month



Product Specification

Product Name: Industrial Aluminium Profile

Alloy: 6063,6061,6005Material: Aluminum

• Suface Treatment: Mill Finished, Anodized , Electrophoretic

Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

• Temper: T4, T5, T6, T66

• Highlight: 6063 metal extrusion profiles,

anodized cylinder metal extrusion profiles ,

6063 aluminum extrusion sections



Product Description

Anodized Industrial Aluminum Profile / Aluminum Cylinder Profile

Material	6061,6063,6005,6082,6060
Process Technology	Extruding ,Machining ,Surface Treatment
Finish	Deburring, Machining
Surface Treatment	Shot blasting, Anodic oxidation, Sand blasting, Painting, Powder coating etc.
Services	OEM/ODM
Certification	ISO9001:2008
Package	Pallet, Carton, Wooden cases ,as inquiry or standa

Order,payment,terms,shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.)Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment: L/C,T/T

Applications:

Aluminum extrusion profiles we supply: For windows ,doors ,fence , screen,Louver, Curtain Wall,handrail,partition ,sunroom ,wardrobe, solar panel frames, exhibit shelf profile, LED Frames, production facility etc.

Competitive Advantage:

- 1. good quality aluminium profile with economic price
- 2. 15-year manufacturing experience
- 3. ISO9000
- 4. ODM or OEM







FAQ For Saving Your Precious Time!

Q1:What's the thickness for anodizing?Can you do 15um? A:Our normal thickness is about 10 um.Yes, we can do 15um and above.

Q2:What color you can do for powder coating?The thickness for powder coat?

A:We can do any color for powder coat as long as you can provide the color sample.Our normally powder coating thickness is 60-80um.

Q3:What color you can do for wood grain?

A:Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc.If you need any other colors, we can do according to the color samples you provide.

Q4:How's the weather resistance for wood grain finish D1010?

A:(1).Powder:Akzo Noble Interpon D1010.

- (2). Wood grain film: Italian Menphis.
- (3). Standard complied: American AAMA Standard. 2603
- (4).UV test:1000 hours.
- (5). Salt spraying test: 1000 hours.
- (6). Normal weather: 10 years color guarantee.

Q5:What certification do you have?What's your standard?

A:We have ISO certification. Our standard is DIN, AAMA, AS/NZS, China GB.

Q6:What's the delivery time for samples and mass production?

- A:(1).2-3 weeks to make the new moulds and make free samples.
- (2).3-4 weeks after receipt of deposit and confirmation of the order.

→ HENTEC Hentec Industry Co.,Ltd



+86-13861643436



aluminum@hentec.com.cn



aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421