Our Product Introduction

Hentec Industry Co.,Ltd aluminumextrusion-profiles.com

10mm - 250mm Polished Industrial Aluminium Profile, Architectural **Aluminium Profiles**

Basic Information

. Place of Origin: China НТ . Brand Name:

CA ,CE ,ISO14001:2004, ISO9001:2000 · Certification:

HTL002 Model Number: • Minimum Order Quantity: 1 ton

Ep paper ,kraft ,pallet Packaging Details:

. Delivery Time: 20days • Payment Terms: T/T ,L/C

Supply Ability: 100 000ton each month



Product Specification

• Product Name: Industrial Aluminium Profile

• Alloy: 6063,6061,6005 • Material: Aluminum

Suface Treatment: Mill Finished, Anodized , Electrophoretic

Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

T3, T4, T5, T6 Temper:

· Highlight: aluminum extrusion profiles,

aluminium extruded profiles



Product Description

10mm - 250mm Polished Industrial Aluminium Profile , Architectural Aluminium Profiles

Specifications

1.Factory directly price

2.ISO,EN,GB... certificates

3. Various surface treament, colour, alloy and use widel

Which Aluminium Profiles We could supply

Alloy:6063, 6061, 6082, 6060, 6005,

Temp:T4, T5, T6

 $Finish: Mill\ finish,\ Anodized, Powder\ coated, Electrophoresis, Wooden\ grain.$

Extrude size:10mm-250mm

Technology Supports

Engineering design

Autocad drawing

Aluminium profiles deeply processing:cutting,punching,drilling,milling,dending and fabricating

Export Experience:17 Years All Over The World.

Five 15-Tons Hot Top Refining Stoves.

Maximum Billet Diameter: ¢320mm

Extrusion System

Shapes: Various Shapes. In Agreement With Design Draings Or Samples.

Maximum Cross Section Width And Cut Length: 410mm And 13mm.

Presses And Tonnage: 30 Extrusion Machines Imported From Taiwan And Europe, 600 To 4000 Us Tons.

Production Capacity:300,000 Tons Per Year.

Standardization :EN755,EN12020,ASTM B221,ANSIH35.2

Anodizing System

Facilities: Six Anodizing Production Lines Made In Taiwan.

 ${\tt Colors: Silver, Champaign, Bronze, Black, Stainless, Gold, Platinum, etc.}$

Maximun Film Thickness:35um

Standardization: QUALANOD, EN12373, ..

公司图号	ĦĦ	线密度 kg/m	公司图号	# #	线密度 kg/m
HT-745	40	1.292	HT-752	40 40 40 47 47 47 47 47 48.2	1.646
HT-746	30	0.786	HT-753	80 8.2 10.2	2.952
HT-747	50	2.524	HT-754	45 200 3	2.015
HT-749	20	0.464	HT-767	45 72 10.2	1.522
HT-750	7.2 40 6.2	0.808			
HT-751	60 8.2 10.4	1.616			

Competitive Advantage:

- $1) Engineering \ design \ and \ support.$
- $2) A luminum\ profiles\ deeply\ processing: cutting, punching, drilling, milling, and\ fabricating.$
- 3) High Quality system, strictly inspection during production and whole inspection before package.
- 4)Good performance, product warranty for 15 years.









