Our Product Introduction

Hentec Industry Co.,Ltd aluminumextrusion-profiles.com

Steel / Mill Finished Anodized Aluminum **Tube**

Basic Information

. Place of Origin: China НТ . Brand Name: CA,CE · Certification: Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Anodized Aluminum Tube

• Alloy: 6063,6061,6005 • Material: Aluminum

Suface Treatment: Mill Finished, Anodized , Electrophoretic

Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

• Temper: T3, T4, T5, T6

· Highlight: aluminum extruded tubing, extruded aluminum profiles



Product Description

Steel / Mill Finished Anodized Aluminum Tube

- 1.Alloy:6063,6061,6005 or according to customer's choice
- 2.Material:Aluminum
- 3.Suface Treatment: Mill Finished, Anodized , Electrophoretic coated, Powder spray coated, Fluorocarbon powder spray coated /PVDF Paint, Drawbench, Steel polished, Wood grain coated /Wooden transfer .
- 4.Deep process: Milling, Drilling, Bending, Cutting.
- 5. Color:clear, satin, bronze, black, golden, silver, other multicolor
- 6.Temper: T4, T5, T6 ,T66

Description:

| Item | Mill Finished Aluminum Extrusion Round Tube |
|--------------|---|
| Material | Alloy 6063, 6061 or according to customer's choice |
| Temper | T3, T4, T5, T6 |
| Surface | Anodize (clear, satin, bronze, black, golden, silver, other multicolor), electrophoresis, powder coating, PVDF coating, wood grain painting, etc. |
| MOQ | 1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container. |
| Profile type | Industry Aluminum profile used in cars, trains machinery ,trailers ,electronics, medical and other industrial filed . |
| Machining | 1. milling; 2. Drilling; 3. Bending; 4. Cutting |
| Moulding | Using our moulds, free; 2. Using customer's drawing, opening mould fee need to be paid. |
| Certificate | ISO14001:2004, ISO9001:2000 |
| FOB Port | Shanghai, etc. |

Applications:

Industry Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed. In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

Specification:

1.Primary Technical Data

1)Chemical composition

| Alloy | Si | Fe | Cu | Mn | Mg | Cr | Zn | Ti | Impurity | Al |
|-------|---------|---------|----------|------|----------|-----------|------|------|----------|------|
| 6063 | 0.2-0.6 | 0.35 | 0.1 | 0.1 | 0.45-0.9 | 0.1 | 0.1 | 0.1 | 0.15 | Rest |
| 6061 | 0.4-0.8 | 0.7 | 0.15-0.4 | 0.15 | 0.8-1.2 | 0.04-0.35 | 0.25 | 0.15 | 0.15 | Rest |
| 6060 | 0.3-0.6 | 0.1-0.3 | 0.1 | 0.1 | 0.35-0.6 | - | 0.15 | 0.1 | 0.15 | Rest |
| 6005 | 0.6-0.9 | 0.35 | 0.1 | 0.1 | 0.40-0.6 | 0.1 | 0.1 | 0.1 | 0.15 | Rest |

2)Mechanical property

| Alloy | Temper | Tensile strength | Yield strength | Elongation |
|-------|--------|------------------|----------------|------------|
| 6063 | T5 | ≥ 160Mpa | ≥ 110Mpa | ≥ 8% |
| 0003 | T6 | ≥ 205Mpa | ≥ 180Mpa | ≥ 8% |
| 6061 | T6 | ≥ 265Mpa | ≥ 245Mpa | ≥ 8% |

2.Specifications:



| G518 L0530 G608 G616 L0574 | 12 16 17 17.6 | 1.7 1.5 4 | 0.149 0.204 |
|--|------------------------|-----------------|----------------|
| L0530 G608 G616 | 17 17.6 | 4 | |
| G608 G616 | 17.6 | | 0.444 |
| G616 | | | 0.441 |
| | 19 | 2 | 0.266 |
| L0574 | | 2 | 0.289 |
| | 19.05 | 1.27 | 0.193 |
| L0567 | 22 | 2 | 0.341 |
| G524 | 22 | 2.2 | 0.371 |
| G400 | 24 | 5.725 | 0.570 |
| L0521 | 24.4 | 2.5 | 0.490 |
| L0515 | 25 | 3 | 0.562 |
| L0551 | 25.2 | 1.6 | 0.322 |
| G419 | 25.4 | 2.03 | 0.404 |
| G550 | 25.4 | 3 | 0.572 |
| G473 | 28 | 1 | 0.230 |
| G587 | 28 | 3.5 | 0.730 |
| L0522 | 28 | 2.5 | 0.570 |
| G418 | 29 | 1.725 | 0.401 |
| L0503 | 30 | 1.4 | 0.364 |
| L0531 | 30 | 2 | 0.501 |
| G661 | 30.2 | 2.2 | 0.524 |
| G251 | 31.8 | 3 | 0.736 |
| L0516 | 32 | 3 | 0.741 |
| L0512 | 33.4 | 3.4 | 0.864 |
| L0553 | 34 | 2 | 0.545 |
| L0523 | 34 | 2.5 | 0.704 |
| L0532 | 37 | 2.3 | 0.714 |
| L0511 | 37 | 3.5 | 0.983 |
| L0564 | 37.2 | 1.6 | 0.485 |
| L0581 | 38 | 1.72 | 0.532 |
| G108 | 38 | 2.5 | 0.756 |
| L0533 | 38 | 3.5 | 1.080 |
| L0509 | 42 | 6 | 1.839 |
| L0540 | 42.15 | 3.53 | 1.217 |
| L0534 | 44.5 | 3 | 1.113 |
| | | | - |

Competitive Advantage:

- 1) Engineering design and support.
- 2) Aluminium profiles deeply processing: cutting, punching, drilling, milling, and fabricating.
- 3) High Quality system, strictly inspection during production and whole inspection before package.
- 4)Good performance, product warranty for 15 years.









