



Anodized Industrial Aluminum Profile Alloy Extrusion For Electrical Shell

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: MetalPluse
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



Product Specification

- Product Name: Industrial Aluminium Cover
- Alloy: 6063,6061,6005
- Material: Aluminium
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T4, T5, T6 ,T66
- Highlight: **Anodized Industrial Aluminum Profile, aluminum alloy extrusion profile, industrial aluminum extrusion For Electrical Shell**



Product Description

Anodized Industrial Aluminum Profile For Electrical Shell

1. Made of Al6063;
2. Slots in the extrusion enclosure for fixing PCB and components and parts;
3. Surface treatment: anodizing, painting, powder coating, etc;
4. Good show on electro magnetic compatibility(EMC), corrosion resistance, fine appearance, good dissipation;
5. Color: Black, silver, grey, etc (can be customized as on request);
6. Widely used in communication, medical treatment, photo-electric, safety, instruments and meters.

Order,payment,terms,shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.)Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment: L/C ,T/T

Applications:

Aluminum extrusion profiles we supply: For windows ,doors ,fence , screen,Louver, Curtain Wall,handrail,partition ,sunroom ,wardrobe, solar panel frames, exhibit shelf profile, LED Frames, production facility etc.

Competitive Advantage:

- 1.good quality aluminium profile with economic price
- 2.15-year manufacturing experience
- 3.ISO9000
- 4.ODM or OEM



FAQ For Saving Your Precious Time!

Q1:What's the thickness for anodizing?Can you do 15um?

A:Our normal thickness is about 10 um.Yes, we can do 15um and above.

Q2:What color you can do for powder coating?The thickness for powder coat?

A:We can do any color for powder coat as long as you can provide the color sample.Our normally powder coating thickness is 60-80um.

Q3:What color you can do for wood grain?

A:Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc.If you need any other colors, we can do according to the color samples you provide.

Q4:How's the weather resistance for wood grain finish D1010?

A:(1).Powder: Akzo Noble Interpon D1010.

(2).Wood grain film: Italian Memphis.

(3).Standard complied: American AAMA Standard.2603

(4).UV test:1000 hours.

(5).Salt spraying test:1000 hours.

(6).Normal weather:10 years color guarantee.

Q5:What certification do you have?What's your standard?

A:We have ISO certification.Our standard is DIN, AAMA, AS/NZS, China GB.

Q6:What's the delivery time for samples and mass production?

A:(1).2-3 weeks to make the new moulds and make free samples.

(2).3-4 weeks after receipt of deposit and confirmation of the order.



 +86-13861643436

 aluminum@hentec.com.cn

 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421