

Powder Painted Aluminium Window Extrusion Profiles 6060 For Elevator

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Model Number: HD50
- Minimum Order Quantity: 1 ton
- Packaging Details: EP Paper ,kraft and pallet
- Delivery Time: 20days
- Payment Terms: T/T or L/C
- Supply Ability: 100 000 ton each month



Product Specification

- Material: Aluminum Alloy
- Temper: T5
- Surface: Powder Painted
- Alloy: 6063 / 6061 / 6060
- Standard: GB/75237-2004, Q/320281/PDWD-2008
- Logo: Printed , Laser Cutting
- Highlight: **Powder Painted Aluminium Window Extrusion Profiles**
, Aluminium 6060 Window Extrusion Profiles,
Elevator Aluminum Extrusion Profiles



Product Description

Description:

Powder Painted Aluminium Window Extrusion Profiles / Elevator Aluminum Profile

Type Option: Sliding, Casement, Fixed, Arch, Tilt & Turn, Awning, Folding, Louver, Circle and etc

Color: As your request

Size: As your request

Frame Material: China brand Aluminum profile with more than 1.4mm thickness for window and 2.0mm thickness for door

Aluminum Option: Normal aluminum profile, Thermal-Break aluminum profile

Glass Option: Clear glass, Laminated glass, Tinted glass, Low-E glass, Frosted glass, all tempered glass

Single layer glass: 4mm, 5mm, 6mm, 8mm, 10mm, 12mm and etc

Double layer glass: 5+9A+5mm, 5+12A+5mm, 6+12A+6mm and etc

Triple glass: 6+9A+6+9A+6mm and etc

Opening Method: Inwards or Outwards, right or left hand opening as your request

Mosquito Screen: Metal and Nylon material for option

Roller shutter: Optional

Surface Treatment: Powder coating, anodizing, electrophoresis coating

Applications

Used in casement doors and windows for living room, dinner room, bathroom, office room, meeting room, restaurant, hotel, etc.

Specifications:

1.Primary Technical Data

1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

2. Specifications :

型号名称	简图	T (mm)	线密度 kg/m	型号名称	简图	T (mm)	线密度 kg/m
PC5010 外框		1.4	0.648	PC5012DN2 加强中框		2.0	1.733
		2.0	0.803				
PC5011 外框		1.4	0.548	PC5013N 横中框		1.4	1.181
		2.0	0.703			2.0	1.432
PC5011N3 外框 角码:LB729		1.4	0.783	PC5013DN1 加强中框		2.0	1.806
PC5012 中框		1.4	0.912	PC5014 中悬窗盖板 角码:PC5037		1.4	1.116
		2.0	1.163				
PC5012N 横中框		1.4	1.112	PC5020 窗扇 角码: 1.4配PC5035 2.0配PC5036		1.4	0.806
		2.0	1.363			2.0	1.087
PC5012N1 加强中框		1.4	1.163	PC5021 门扇 角码:LB730		1.5	1.101
						2.0	1.287

[window and door P17-18.pdf](#)

[window and door P19-20.pdf](#)

[window and door P21-22.pdf](#)


[window and door P23-24.pdf](#)

[window and door P25-26.pdf](#)

[window and door P27-28.pdf](#)

Competitive Advantage:

- 1)Engineering design and support.
- 2)Aluminium profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
- 3)High Quality system, strictly inspection during production and whole inspection before package.
- 4)Good performance, product warranty for 15 years.



Hentec Industry Co., Ltd



HENTEC Hentec Industry Co.,Ltd

☎ +86-13861643436 ✉ aluminum@hentec.com.cn 🌐 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421