# 40x40 6063 T5 Industrial Extruded Heavy Duty T-Slot Aluminum Extrusion **Profile**

### **Basic Information**

. Place of Origin: China . Brand Name: Hentec SGS · Certification: Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month

## **Product Specification**

• Product Name: Industrial Aluminium Profile

• Alloy: 6063,6061,6005 • Material: Aluminum

Suface Treatment: Mill Finished, Anodized , Electrophoretic

Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

T4, T5, T6, T66 • Temper:

· Highlight: **Aluminum Extrusion Profile**,

6063 T Slot Aluminum Profile,

**Electrophoretic T Slot Aluminum Profile** 

#### **Product Description**

#### 40x40 6063 T5 Industrial Extruded Heavy Duty T-Slot Aluminum Extrusion Profile

Except the standard profiles, we offers service from tooling design for customized project, extrusion production, assembling, cutting, drill threading till packaging, give assistance for our customer to develop the new style and functional products. Welcome for customized Extrusion Aluminum for multiple industrial application, like window & doors, heat sink, building systems, precision tubing, flat extrusion profiles, complex extrusion profiles, Radiator, Assembly line, Frame system, Conveyors, Workbench, Machine Guards, Stairs & Platforms, Metal Fence, Display rack, Automotive, Motor aluminum housing, Bridge system, Vessel, Elevator, etc.

- 1. Reliable quality (ISO9001:2008 certified).
- 2. Competitive prices with short lead-time for both tooling and parts, because we do everything in-house.
- 3. Effective and strong technical support and excellent sales services.
- 4. Sufficient production capacity (only 65% occupied).
- 5. Efficient communication (48-hour quote lead time).
- 6. Compliant with RoHS Test.

Material:	Aluminum alloy 6063, 6061
Temper:	T5, T6
Finish:	mill finish, anodized, powder coated, electrophoresis, fluorocarbon spray-painting, wooden grain, polishing, hairy, sand blasting etc.
Max Length:	7.2m
Thickness:	0.8mm~3.0mm (0.8/1.0/1.2/1.4/1.6/2.0mm)
Standard:	ISO9001, ISO14001, SGS, AAA
Color:	Silver, champagne, bronze, brass, black etc (Per your request).
Packing:	Protective Film+ Kraft / EPE Foam (Per your request).
Production Time:	25~30 days after deposit
Production Capacity:	1000,000 Ton/Year
MOQ:	1 TON
Port:	Shanghai
Certificate:	ISO9001,ISO14001,SGS,OHSAS 18001,USA STANDARD AAMA 2603,AAMA2604,AAMA2605,UK STANDARD BS6496,JAPANESE STANDARD JISH4100,JISH8600,JISH8602
Product Advantage	Weather proofing, Durable, Easy cleaning, Excellent Fire egress, Energy efficient glass and 10 years guarantee

#### Order,payment,terms,shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.) Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment: (Can negotiate with customers, our usual practices are as follow)
- 4, Tooling:100% prepaid by T/T.
- 5, Parts:30% upon order confirmation and balance before delivery by T/T

#### **Applications**

Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

### **Competitive Advantage:**

- 1. good quality aluminium profile with economic price
- 2. 15-year manufacturing experience
- 3. ISO9000
- 4. ODM or OEM



# **⇒HENTEC** Hentec Industry Co.,Ltd



+86-13861643436





aluminum@hentec.com.cn aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421