Anodized 6063 Aluminium Profile System Aluminium T Slot Frame Profile Extrusion

Basic Information

. Place of Origin: China . Brand Name: MetalPlus

CA ,CE ,ISO14001:2004, ISO9001:2000 Certification:

Minimum Order Quantity:

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20days T/T ,L/C • Payment Terms:

• Supply Ability: 100 000ton each month



Product Specification

• Product Name: Industrial Aluminium Profile

• Alloy: 6063 • Material: Aluminum

Suface Treatment: Mill Finished, Anodized Powder Spray Coated

• Deep Process: Milling, Drilling, Cutting

• Temper:

Extrusion Aluminium T Slot Frame, • Highlight: Mill Finished Aluminium T Slot Frame,

Mill Finished 6063 Aluminium Profile



More Images



Product Description

Anodized 6063 Aluminium Profile System / Aluminium T Slot Frame Profile Extrusion

It's widely used in making aluminum frame, Surface treated with positive oxidation, Beautiful and corrosion resistant, usually use bolt for inside connection. It's one of profiles which is most widely used in industrial framework.

Product Specification

OII
Aluminum Assembly Line
Aluminium 6000 series alloy, such as 6061, 6063,6060,6005 6082 etc.
T5, T6
Customized.
Square, flat, round, hollow, oval, triangle, U-profile, L-profile, T-profile, H-profile, customized available.
Anodizing , Powder Painting , Mill Finished
Silver, champagne, black, bronze, gold, white or customized
Window and door with thermal break strips, curtain wall, glass wall, furniture, ceiling, kitchen, LED strip, transportation rail, vehicle, motor housing, machine, tent, solar panel, industrial profile, decoration profile etc.
CNC, drilling, milling, cutting, tapping, welding, bending, assembling.
500 kgs for each item, usually 13-15 tons for a 20GP, 25-28 tons for a 40HQ.
Drawing, sample or design service offer by customer.
2400-3000 Metric tons monthly.
MetalPlus
1) ISO9001-2008/ISO 9001:2008; 2) CQM CERTIFICATES; 3) SGS, CE, BV, JIS, AS, NZS, QUALICOAT, QUOLANOD AVAILABLE.
Surface color can be stable for 10-20 years indoor using.
Inside: pack with EP foam Outside: craft paper ,Pallet , Wooden Case
Die developing and sample testing: 12-18 days .
Mass production: 25-30 days after confirming sample by buyer.
Shanghai Port
T/T 30% for deposit, balance before delivery.



Factory Capacity:

Die Center

CNC cutting: 5 sets CNC lathe:2 sets

CNC machining center: 15 sets

Extrusion Lines

Extrusion lines: 22sets imported from Japan, Italy with annual capacity 400 thousands of tons.

Anodizing Lines

With 2full-automatically horizontal type and 1 vertical type.

The oxidize aluminum materials length is up to 10m, electrophoretic materials length is up to 7.5m, with an annual output of 150,000tons.

Powder coating lines

With 2powder coating lines from Italy and 4sets of guns from Switzerland

Applications:

Industry Aluminum profile used in assembly production line , electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products.



Specifications:

1.Primary Technical Data

1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2)Mechanical property

Alloy	Hemner	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
0003	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

公司图号	# 16	线密度 kg/m
HT-745	40	1.292
HT-746	30	0.786
HT-747	50	2.524
HT-749	20 20 20 20 20 20 20 20 20 20 20 20 20 2	0.464
HT-750	7.2 40 6.2	0.808
HT-751	60 8.2 10.4	1.616

公司图号	# 16	线密度 kg/m
HT-752	40	1.646
HT-753	80 8.2 10.2	2.952
HT-754	45 2 0 5 1 0 0 5 1 0 0 1	2.015
HT-767	12.7 25.7 15.2 15.2 15.2 15.2 15.2 15.2 15.2 15.2	1.522

Competitive Advantage:

- 1)Engineering design and support.
 2)Aluminum profiles deeply processing:cutting,punching,drilling,milling,and fabricating.
 3)High Quality system, strictly inspection during production and whole inspection before package.
 4)Good performance, product warranty for 15 years.





⇒HENTEC Hentec Industry Co.,Ltd



+86-13861643436





Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421