# Hentec Industry Co.,Ltd aluminumextrusion-profiles.com

## Customized CNC Machining 6000 Series T3-T8 Temper 60 Series Aluminium T Slot Profile Extrusion Profile

#### **Basic Information**

Certification: CE, ISOMinimum Order Quantity: 500Price: 2.99



#### **Product Specification**

Model NO.:
T Slot Profile Extrusion

Shape: T - Profile
Grade: 6000 Series
Temper: T3-T8
Alloy: 6063

Surface Finishing: Anodic OxidationSurface Treatment: Sandblasting Anodized

• Specification: 20\*20, 30\*30, 40\*40, 40\*80, 30\*60,

80\*80mm

• Chemical Composition: Si: 0.2-0.6, Fe: 0.35, Cu: 0.1, Mn: 0.1, Mg:

0.45-0.9, Cr: 0.1, Zn: 0.1, Ti: 0.1, Impurity:

0.15, Al: Rest

Tensile Strength: ≥ 160Mpa (T5), ≥ 205Mpa (T6)
Yield Strength: ≥ 110Mpa (T5), ≥ 180Mpa (T6)

• Elongation: ≥ 8%

Production Capacity: 100000 Ton/ Year



#### More Images









#### Customized CNC Machining Anodized 6063 Aluminium T Slot Profile Extrusion Profile

#### **Product Specifications**

Parameter	Details				
Size	10/15/20/25/30/35/40/45/50/55/60/65/70/75/80/85 series and Custom Made sizes				
Grade	6061/6063-T5/T6				
Standard	GB/5237-2004				
Certification	ISO9001, RoHS, SGS				
Material	Aluminum				
Color	Clear, Black, any custom-made colors available				
Surface Treatment	Mill finish, Anodizing, Sand Blasting, Powder Coating, etc.				
Deep Processing	Machining, Cutting, Drilling, Threading, Bending, etc.				
Applications	Building, Industry, Machinery, Assembly stations, Cellular manufacturing workstations, Linear motion devices				

#### **Chemical Composition**

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

#### **Mechanical Properties**

Alloy	Temper	Tensile Strength	Yield Strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
6063	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

#### Packaging & Shipping

Packaging: Standard export package, with options for custom packaging per client requirements.

#### Shipping Options:

Samples shipped via express (FEDEX, DHL, UPS, EMS) with freight paid by client

Mass production shipped FOB Shanghai with freight negotiated based on specific conditions

Delivery Time: 3 weeks after confirming all order details

#### **Company Profile**

Since 2007, MetalPlus has operated a 3600-ton extrusion press capable of producing heat sinks up to 600mm in diameter. We specialize in custom aluminum extrusions for construction and industrial applications, offering complete services from mold design to fabrication and surface treatment.

#### Certifications

### **Company Milestones** 2004: Recognized Brand of the Building Industry Material Market 2006: ISO9001 Certification and Product Exemption from Quality Surveillance Inspection 2009: Jiangsu Famous Brand Certificate and Advanced Company recognition 2012: Established partnerships with Panasonic and LG 2015: Became innovative producer and supplier for European clients 2017: Developed new baseboard heater products 2019: Supplier to world's largest heater manufacturers 2023: Expanding global distributor network **Notable Projects** Soccer City Stadium, Johannesburg As primary aluminum supplier for Africa's largest stadium (94,000 seats), we contributed to this landmark project that received widespread acclaim upon completion. **Lobster Trailers Partnership** Our collaboration with this Nordic trailer manufacturer combines our R&D expertise with precision processing to optimize designs and reduce production costs while enhancing performance.

#### **Educational Furniture Supply**

Supplied aluminum legs for school desks as part of a major educational project, demonstrating our capability to support institutional clients with customized solutions.

#### **→ HENTEC** Hentec Industry Co.,Ltd



+86-13861643436



aluminum@hentec.com.cn



aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421