



## T5 / T6 Blinds Aluminum Window Frame Extrusions Gold Color ROHS

Our Product Introduction

for more products please visit us on [aluminumextrusion-profiles.com](http://aluminumextrusion-profiles.com)

### Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: EP Paper ,kraft and pallet
- Delivery Time: 20days
- Payment Terms: T/T or L/C
- Supply Ability: 100 000 ton each month



### Product Specification

- Material: Aluminum Alloy
- Temper: T5 / T6
- Alloy: 6063 / 6061 / 6060
- Surface: Anodized
- Color: Gold
- Highlight: **aluminum extrusion profiles,  
extruded aluminium profiles**



## Product Description

### Detailed Product Description

Product Name:	Extrusion Profile	Application:	Construction
Color:	Green	Alloy:	6063-T5
Temper:	T5	Film Thickness:	AA10 , AA15
Standard:	ROHS	Surface:	Powder Painted

We have a good design team, we can open mould for your special requirements.

### Powder Painted Aluminum Extrusion Profiles , Aluminum Profile For Blinds

Alloy:	6063	6061	6060	6005	6082	
Temper :	T5	T6	T4			
Standard:	DIN	AAMA	AS	CHINAGB		
Certification:	ISO9001: 2008.					
Surface Finish:	Mill finish	Anodizing	Powder Coating	Wood Grain	Electrophoresis	Polished
Color:	Anodizing:	Silver, bronze, champagne, titanium, nickel, golden yellow, etc. Anodizing thickness is up to 25um.				
	Powder Coating:	White, black, bronze, grey, green, etc . Powder coating thickness is more than 60um.				
	Wood Grain:	1. Italian MENPHIS transfer printing paper. 2. AKZO NOBEL INTERPON D1010(10 years warranty): Australia cedar, Bush cherry, Chest nut, Jarrah I, Jarrah II, Western red cedar, etc. 3. AKZO NOBEL INTERPON D34(5 years warranty): Bush wood, Western red, Jarrah, Snow gum, etc.				
	Electrophoresis:	Silver, nickel, golden yellow, black, champagne, etc				
	Polishing	Silver, nickel, golden yellow, black, etc				
	Brushing:	Silver, nickel, golden yellow, black, bronze, etc				
	Machining:	Cutting, punching, drilling, bending, weld, mill, CNC, etc.				
OEM customized aluminium profiles are available.						

### Professional Working team

<b>2D&amp;3D Design</b>	1: 4 Designers in design and development department 2: Auto CAD, 3D, AI, SLD, PRT. IGS, PDF, JPEG etc.
<b>Engineering&amp; Tooling</b>	1: 8 Engineers in Mold Shop. 2: Use high tonnage extruder, Wire EDM, CNC, Drilling machines etc.
<b>Quality Control</b>	1.ISO Approved. 2.Inspection at Site. 3.Inspection Before Shipping. 4.Testing Machine.
<b>Packing details</b>	1.EP Paper inside for each profile separate then craft paper outside 2.EP Paper inside for each profile separate then carton paper then pallet 3. Shrink film 4.wooden carton
<b>Delivery</b>	15-25days after receiving down payment
<b>Payment Term</b>	T/T , L/C

### Applications:

Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

### Competitive Advantage:

- (1). Suitable for widely application .
- (2). 20 years warranty.
- (3). High corrosion resistance.
- (4). 5-10 years weather resistance.
- (5). Good wear resistance & anti-scratch.
- (6).Size customized.



#### FAQ For Saving Your Precious Time!

Q1: What's the thickness for anodizing? Can you do 15um?

A: Our normal thickness is about 10 um. Yes, we can do 15um and above.

Q2: What color you can do for powder coating? The thickness for powder coat?

A: We can do any color for powder coat as long as you can provide the color sample. Our normally powder coating thickness is 60-80um.

Q3: What color you can do for wood grain?

A: Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc. If you need any other colors, we can do according to the color samples you provide.

Q4: How's the weather resistance for wood grain finish D1010?

A: (1). Powder: Akzo Noble Interpon D1010.

(2). Wood grain film: Italian Memphis.

(3). Standard complied: American AAMA Standard.2603

(4). UV test: 1000 hours.

(5). Salt spraying test: 1000 hours.

(6). Normal weather: 10 years color guarantee.

Q5: What certification do you have? What's your standard?

A: We have ISO certification. Our standard is DIN, AAMA, AS/NZS, China GB.

Q6: What's the delivery time for samples and mass production?

A: (1). 2-3 weeks to make the new moulds and make free samples.

(2). 3-4 weeks after receipt of deposit and confirmation of the order.

 **HENTEC** Hentec Industry Co.,Ltd

 +86-13861643436

 aluminum@hentec.com.cn

 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421