HENTEC Hentec Industry Co.,Ltd aluminumextrusion-profiles.com

Sand Blasting Aluminum Heatsink Extrusion Profiles Aluminum Extrusion **Radiator**


Basic Information

. Place of Origin: China . Brand Name: HT CA,CE · Certification: KTH-007 Model Number: • Minimum Order Quantity: 1 ton

Ep paper ,kraft ,pallet Packaging Details:

. Delivery Time: 20days • Payment Terms: T/T ,L/C

Supply Ability: 100 000ton each month



Product Specification

• Product Name: Aluminum Heatsink Extrusion Profiles

• Alloy: 6063,6061,6005 • Material: Aluminum

Mill Finished, Anodized , Electrophoretic Suface Treatment:

Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

T4, T5, T6, T66 • Temper:

· Highlight: heatsink extrusion profiles,

aluminium heatsink extrusion

Product Description

Descrition:

6063 - T5 Aluminum Heatsink Extrusion Profiles , Aluminum Extrusion Radiator

We can supply kinds of aluminum heat sink with different kinds of material, specifications and surface treatments.

- 1. Material: 6063, 6061, 6005 etc.
- 2. surface treatment: anodizing, powder coating, polishing, mill finishing, sand blasting, wire drawing, wood color (timber turning) (as per customer requirements)
- 3. Procedure: preciously cutting, milling, drilling, punching, CNC machining,tapping, deburring, etc..

Customers'own detailed drawings or samples are welcome. Any OEM is welcome.

Order,payment,terms,shipment

- 1, Minimum order: 500 kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.)Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment :30% T/T in advance the balance after the copy of BOL .

Applications:

Aluminum heat sink is widely used on Machines, cars, lighter...

Specifications:

- 1. Primary Technical Data
- 1)Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

- 1	=)ooaoa.	p. 0 p 0. t)				
H	Alloy	Temper	Tensile	Viold strangth	Elongation	
	Alloy	l'emper	strength	rieid strengtii		
	6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%	
	0003	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%	
	6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%	



- Competitive Advantage:
 1) low price and high quality; High Quality CNC machining / extrusion / forging / die casting aluminum heat sinks
 2) Small orders accepted;
 3) Closely tolerance;



⇒HENTEC Hentec Industry Co.,Ltd



+86-13861643436





Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421