HENTEC Hentec Industry Co., Ltd aluminumextrusion-profiles.com

Clear Extruded Aluminum Framing Length 1m - 13m Polishing 2.5m


Basic Information

Place of Origin: China
Brand Name: HTS-455
Certification: SGS
Minimum Order Quantity: 1 ton

Packaging Details: Ep paper ,kraft ,pallet

Delivery Time: 20daysPayment Terms: T/T ,L/C

• Supply Ability: 100 000ton each month



Product Specification

Product Name: Industrial Aluminium Profile

Alloy: 6063,6061,6005Material: Aluminum

Suface Treatment: Mill Finished, Anodized , Electrophoretic

Coated, Powder Spray Coated

• Deep Process: Milling, Drilling, Bending, Cutting

Temper: T4, T5, T6, T66
 Highlight: aluminium door frame, aluminium extruded profiles

Product Description

Descrition: Clear Anodized Industrial Aluminum Profiles , Aluminum Profile for Cylinder

Architecture Profile : GB 5237-2008 Production Standard: Industry Profile : GB/T6892-2008 Aluminum extrusion profiles for architectural & industrial, Different aluminum profile sections for different applications . Main products Aluminum Formwork for Building Construction. Mill finish,powder coating,anodized color,wooden pattern,Polyvinylidene Fluoride (PVDF)-Coating,Machine Polishing, Chemical Polishing, Mirror Polishing, Brushing Finish,thermal insulation of barrier strip,thermal insulation of filling-polyurethane Based on Guangdong Nanhai Lingtong Aluminium Ingot price +different finishes processing Fee + local cost 7 Price: Payment term: 7 A. Alioy: 6063, 6060, 6061, 6005 etc B. State: T5/T6 C. Length: 1m-13 m (polishing : 2.5 m) D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. MOC: 1 X20 FCL _Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid.			
Production Standard: Industry Profile : GB/T6892-2008 Aluminum extrusion profiles for architectural & industrial, Different aluminum profile sections for different applications . Main products Mill finish, powder coating, anodized color, wooden pattern, Polyvinylidene Fluoride (PVDF)-Coating, Machine Polishing, Chemical Polishing, Mirror Polishing, Brushing Finish, thermal insulation of barrier strip, thermal insulation of filling-polyurethane Based on Guangdong Nanhai Lingtong Aluminium Ingot price +different finishes processing Fee + local cost T/T, L/C at sight A. Alloy: 6063, 6060, 6061, 6005 etc B. State: T5/T6 C. Length: 1m-13 m (polishing : 2.5 m) D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 116 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box, Wooden box etc, Customized package is available. MOQ: 1/20 FCL, Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10 -15 days after drawing confirmed and mold cost paid.	1	Business type:	Real Big Manufacturer & Exporter with 22 years experience
Aluminum extrusion profiles for architectural & industrial, Different aluminum profile sections for different applications . Aluminum Formwork for Building Construction. Mill finish,powder coating,anodized color,wooden pattern,Polyvinylidene Fluoride (PVDF)-Coating,Machine Polishing, Chemical Polishing, Mirror Polishing, Brushing Finish,thermal insulation of barrier strip,thermal insulation of filling-polyurethane Based on Guangdong Nanhai Lingtong Aluminium Ingot price +different finishes processing Fee + local cost Payment term: 177, L/C at sight A. Alloy: 6063, 6060, 6061, 6005 etc B. State: 157/6 C. Length: 1m-13 m (polishing : 2.5 m) D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. MOQ: 1X20 FCL, Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid.	2	Production Standard:	Architecture Profile : GB 5237-2008
Sections for different applications. Aluminum Formwork for Building Construction. Mill finish,powder coating,anodized color,wooden pattern,Polyvinylidene Fluoride (PVDF)-Coating,Machine Polishing, Chemical Polishing, Mirror Polishing, Brushing Finish,thermal insulation of barrier strip,thermal insulation of filling-polyurethane Based on Guangdong Nanhai Lingtong Aluminium Ingot price +different finishes processing Fee + local cost Payment term: 7			Industry Profile : GB/T6892-2008
Aluminum Formwork for Building Construction. Mill finish,powder coating,anodized color,wooden pattern,Polyvinylidene Fluoride (PVDF)-Coating,Machine Polishing, Chemical Polishing, Mirror Polishing, Brushing Finish,thermal insulation of barrier strip,thermal insulation of filling-polyurethane Based on Guangdong Nanhai Lingtong Aluminium Ingot price +different finishes processing Fee + local cost 7			
4 Main Product Finishes (PVDF)-Coating,Machine Polishing, Chemical Polishing, Mirror Polishing, Brushing Finish,thermal insulation of barrier strip,thermal insulation of filling-polyurethane 5 Price: Based on Guangdong Nanhai Lingtong Aluminium Ingot price +different finishes processing Fee + local cost 6 Payment term: T/T, L/C at sight A. Alloy: 6063, 6060, 6061, 6005 etc B. State: T5/T6 C. Length: 1m-13 m (polishing : 2.5 m) D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Rraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. 9 MOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid. 11 Delivery time: 35 days after deposit received.	3	Main products	Aluminum Formwork for Building Construction.
processing Fee + local cost Payment term: T/T, L/C at sight	4	Main Product Finishes	(PVDF)-Coating,Machine Polishing, Chemical Polishing, Mirror Polishing, Brushing Finish,thermal insulation of barrier strip,thermal insulation of filling-polyurethane
processing Fee + local cost 7/T, L/C at sight A. Alloy: 6063, 6060, 6061, 6005 etc B. State: T5/T6 C. Length: 1m-13 m (polishing : 2.5 m) D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. Packing: NOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid.		Price:	Based on Guangdong Nanhai Lingtong Aluminium Ingot price +different finishes
A. Alloy: 6063, 6060, 6061, 6005 etc B. State: T5/T6 C. Length: 1m-13 m (polishing : 2.5 m) D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. MOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid.	5		processing Fee + local cost
B. State: T5/T6 C. Length: 1m-13 m (polishing : 2.5 m) D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. MOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid.	6	Payment term:	T/T, L/C at sight
B. State: T5/T6 C. Length: 1m-13 m (polishing : 2.5 m) D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. MOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid.			A. Allov: 6063, 6060, 6061, 6005 etc
D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. MOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid. 11 Delivery time: 35 days after deposit received.	7		B. State: T5/T6
D. Normal Anodizing thickness: 8-12 micro E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. MOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid. 11 Delivery time: 13 days after deposit received.			C. Length: 1m-13 m (polishing : 2.5 m)
E. Normal powder coating thickness: 60-100 micro F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: WOQ: X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid. 11 Delivery time: 35 days after deposit received.			
F. Tensile strength: ≥ 16 mpa G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: WOQ: MOQ: TX20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid. 11 Delivery time: 35 days after deposit received.			
G. Yield strength: ≥ 110 mpa H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: WOQ: TX20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. Sample time 10-15 days after drawing confirmed and mold cost paid. Delivery time: 35 days after deposit received.			
H. Extensibility: ≥ 8% I. Hardness(HW): ≥ 8 Packing: WOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid. Delivery time: 35 days after deposit received.			
I. Hardness(HW): ≥ 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box,Wooden box etc,Customized package is available. MOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. Sample time 10-15 days after drawing confirmed and mold cost paid. Delivery time: 35 days after deposit received.			
available. 9 MOQ: 1X20 FCL ,Each profile not less than 500 kgs. Each color not less than 2 tons. 10 Sample time 10-15 days after drawing confirmed and mold cost paid. 11 Delivery time: 35 days after deposit received.			I. Hardness(HW): ≥ 8
Sample time 10-15 days after drawing confirmed and mold cost paid. Delivery time: 35 days after deposit received.	8	· ·	
Delivery time: 35 days after deposit received.	9	MOQ:	
	10	Sample time	10-15 days after drawing confirmed and mold cost paid.
12 Port Shanghai Port	11	Delivery time:	35 days after deposit received.
Dianglia i or	12	Port	Shanghai Port

Order,payment,terms,shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.)Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment: L/C ,T/T

Applications:

Aluminum extrusion profiles we supply: For windows ,doors ,fence , screen,Louver, Curtain Wall,handrail,partition ,sunroom ,wardrobe, solar panel frames, exhibit shelf profile, LED Frames, production facility etc.

Competitive Advantage:

- 1. good quality aluminium profile with economic price
- 2. 15-year manufacturing experience
- 3. ISO9000
- 4. ODM or OEM





FAQ For Saving Your Precious Time!

Q1:What's the thickness for anodizing?Can you do 15um? A:Our normal thickness is about 10 um. Yes, we can do 15um and above.

Q2:What color you can do for powder coating?The thickness for powder coat?

A:We can do any color for powder coat as long as you can provide the color sample.Our normally powder coating thickness is 60-80um.

Q3:What color you can do for wood grain?

A:Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc.If you need any other colors, we can do according to the color samples you provide.

Q4:How's the weather resistance for wood grain finish D1010?

A:(1).Powder:Akzo Noble Interpon D1010.

- (2). Wood grain film: Italian Menphis.
- (3). Standard complied: American AAMA Standard. 2603
- (4).UV test:1000 hours.
- (5). Salt spraying test:1000 hours.
- (6). Normal weather: 10 years color guarantee.

Q5:What certification do you have?What's your standard?

A:We have ISO certification. Our standard is DIN, AAMA, AS/NZS, China GB.

Q6:What's the delivery time for samples and mass production?

A:(1).2-3 weeks to make the new moulds and make free samples.

(2).3-4 weeks after receipt of deposit and confirmation of the order.

→ HENTEC Hentec Industry Co.,Ltd







