



## Customerized Aluminum Extrusion Profiles , Reliable Aluminum Enclosure

### Our Product Introduction

#### Basic Information

- Place of Origin: China
- Brand Name: Hentec
- Certification: SGS
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



#### Product Specification

- Product Name: Industrial Aluminium Profile
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T4, T5, T6 ,T66
- Highlight: **aluminium extrusion profiles, aluminium extruded profiles**

## Product Description

### Customerized Aluminum Extrusion Profiles , Reliable Aluminum Enclosure

1. Reliable quality (ISO9001:2008 certified).
2. Competitive prices with short lead-time for both tooling and parts, because we do everything in-house.
3. Effective and strong technical support and excellent sales services.
4. Sufficient production capacity (only 65% occupied).
5. Efficient communication (48-hour quote lead time).
6. Compliant with RoHS Test.

Item	Original Product	Alternatives
Shape	Irregular	Round, Square, Triangle, Rectangle etc...and Customized shapes are welcomed.
Alloy	6063 alloy	6061,6082,6060,6005 Alloy etc.
Temper	T6	T4,T5,T6 can be discussed.
Machining & Fabrication	Not required	Cutting, Shearing, Deburring, Tumbling, Punching, Drilling, Tapping, Chamfering, Cold-drawing, Bending, Stamping, Forming, Polishing, Grinding, Brushing, Sandblasting, Welding Numerical Control Lathing, Milling, Sophisticated CNC Precision Machining
Finishing	Painted	Mill finished, Anodized, Electrophoresis, Powder coated, Painted, Sliver matt, Sand blasted, PVDF, Silkscreened etc.
Standard for Extrusion	GB /T5237-2000	EN-755-2/3/6/8, BS-1474, BS 1161 (British Standards)
		JIS H4100 (Japanese Standard)
		AS/NZS1866-1997 (Australian New Zealand Standard)
Standard for Fabrication	GB/T1804-92	BS 8118 TS1649
Standard for Anodizing	GB5237.2-2004	BS1615:1987
		BS5599:1993
		Mil-A-8625E Type I
		Mil-A-8625E Type III

### Order,payment,terms,shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days(15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab. )Production Lead time: it depends on customers' order quantity ( 30 working days after deposit).
- 3, Payment: (Can negotiate with customers, our usual practices are as follow)
- 4, Tooling:100% prepaid by T/T.
- 5, Parts:30% upon order confirmation and balance before delivery by T/T

### Applications:

Aluminum profile used in cars, trains machinery ,electronics, medical and other industrial filed . In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

### Competitive Advantage:

1. good quality aluminium profile with economic price

2. 15-year manufacturing experience
3. ISO9000
4. ODM or OEM



#### FAQ For Saving Your Precious Time!

Q1:What's the thickness for anodizing?Can you do 15um?

A:Our normal thickness is about 10 um.Yes, we can do 15um and above.

Q2:What color you can do for powder coating?The thickness for powder coat?

A:We can do any color for powder coat as long as you can provide the color sample.Our normally powder coating thickness is 60-80um.

Q3:What color you can do for wood grain?

A:Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc.If you need any other colors, we can do according to the color samples you provide.

Q4:How's the weather resistance for wood grain finish D1010?

A:(1).Powder: Akzo Noble Interpon D1010.

(2).Wood grain film: Italian Memphis.

(3).Standard complied: American AAMA Standard.2603

(4).UV test: 1000 hours.

(5).Salt spraying test: 1000 hours.

(6).Normal weather: 10 years color guarantee.

Q5:What certification do you have?What's your standard?

A:We have ISO certification.Our standard is DIN, AAMA, AS/NZS, China GB.

Q6:What's the delivery time for samples and mass production?

A:(1).2-3 weeks to make the new moulds and make free samples.

(2).3-4 weeks after receipt of deposit and confirmation of the order.

