



Extruded Oxidize Aluminum Solar Panel Frame For Photovoltaic Module

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Hentec
- Certification: CA ,CE
- Model Number: HT858
- Minimum Order Quantity: 1 ton
- Packaging Details: Packed with EP ,Carton ,Pallet or wooden case
- Delivery Time: 25days
- Payment Terms: T/T ,L/C
- Supply Ability: 3000tons each month



Product Specification

- Material: Aluminum Alloy
- Temper: T5
- Color: Silvery
- Application: Roof
- Size: 40*40mm
- Surface: Anodized
- Highlight: aluminium solar panel frame,
solar panel aluminum frame

Product Description

Extruded Oxidize Aluminum Solar Panel Frame For Photovoltaic Module

Our company Hentec has more than 15 years experience in manufacturing Aluminum and steel components and works strictly under ISO 9001 manufacturing standards . Hentec has a team of engineers ready to not only assist our customer but also their customers with any solar mounting solution design whether it be a small roof or large scale utility solar farm. We have years of experience in layout design, dealing with different soil and wind conditions, and rooftop design .Understanding that the most important part of solar pv solar installations is 'time', all of our products are carefully designed with fast installation always in mind.

Description :

Type:	Ground solar mounting
Installation site:	Open field ground
Material:	Aluminum 6063 T3-T5; Steel
Fasten material:	Aluminum
Anticorrosive:	Hot-dip galvanized
Survival Wind Speed:	< 60m/s
Design Snow load:	Up to 1.4KN/ Square meters
Solar panel type:	Framed or Frameless
Panel Orientation:	Transverse or vertical
Design Standard:	CE; ISO 9001
Quality warranty:	12-25 years
Duration:	More than 20 years
Delivery time:	7-15 days
Package:	Standard Packing

Specifications :

Item	Aluminum Extrusion Solar Panel Frame
Material	Alloy 6063, 6061 or according to customer' s choice
Temper	T3, T4, T5, T6
Surface	Anodize (clear, satin, bronze, black, golden, silver, other multicolor) , electrophoresis, powder coating, PVDF coating, wood grain painting, etc.
Color	Any color based on Standard Germany RAL Mark
MOQ	1 ton. Usually 12 tons for a 20 feet container; 24 tons for a 40 feet container.
Profile type	used as the frame of solar panel
Fabrication	1. Milling; 2. Drilling; 3. Bending; 4. Cutting.
Moulding	1. Using our moulds, free; 2. Using customer' s drawing, opening mould fee need to be paid.
Mould size	25*25, 35*35, 30*46, 46*50, 30*25, 40*40 ,50*35, etc. We can provide customized aluminum solar frames upon to customers' request.
FOB Port	Shanghai, etc.













1. Alloy : 6063, 6061, 6005 or according to customer' s choice
2. Material: Aluminum
3. Surface Treatment: Mill Finished, Anodized , Electrophoretic coated, Powder spray coated, Fluorocarbon powder spray coated / PVDF Paint, Drawbench, Steel polished, Wood grain coated / Wooden transfer .
4. Deep process: Milling, Drilling, Bending, Cutting.
5. Application: Aluminum solar frame is widely used as the frame of solar panel.
6. Color: clear, satin, bronze, black, golden, silver, other multicolor
7. Temper: T4, T5, T6 , T66

新图号 旧图号	简 图	线密度 kg/m	新图号 旧图号	简 图	线密度 kg/m
GT001 G701		0.987	GT007 G007		0.803
GT002 角码为GT001 G702		0.530	GT008 G008		0.633
GT003 G795		0.615	GT009 G009		0.494
GT004 G794		0.466	GT010 G010		0.496
GT005 G590		0.814	GT011 G011		0.388
GT006 G591		0.681	GT012 G012		0.290

新图号 旧图号	简 图	线密度 kg/m	新图号 旧图号	简 图	线密度 kg/m
GT013 G778		0.372	GT019 G599		0.665
GT014 G594		0.367	GT020 G846		0.400
GT015 G595		0.183	GT021 Z081		0.884
GT016 G596		0.248	GT022 Z082		1.228
GT017 G597		0.534	GT023 Z083		0.952
GT018 G598		0.339	GT024 Z084		1.073

线密度仅供参考，出货以实际称重为准！ 210

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT025 角码为GT026		0.653	GT031		0.548
G895			G893		
GT026		0.732	GT032		0.279
G896			G894		
GT027 角码为GT026		0.424	GT033		1.711
G915			G913		
GT028 角码为GT026		0.524	GT034 角码为GT033		0.745
G916			G914		
GT029		1.300	GT035		0.398
G822			G222		
GT030 角码为GT029		0.567	GT036		0.754
G823			G224		

新图号 旧图号	简 图	线密度 kg/m	新图号 旧图号	简 图	线密度 kg/m
GT037 G229		0.172	GT052		0.728
GT038 G230		0.374	GT054 角码为GT052		0.509
GT039 G889		0.626	GT055 角码为GT052		0.537
GT040 G888		0.756	GT061		0.161
GT041 角码为GT026 G187		0.692	GT062		0.340
GT042 角码为GT026 G789		0.443	GT063		0.209

新图号	简图	线密度 kg/m
旧图号		
GT064		0.394
GT068		0.497
GT069		0.613
GT070		0.312
角码为 GT050		
GT071		0.687
GT072		0.378

新图号	简图	线密度 kg/m
旧图号		
GT076		0.698
角码为 GT050		
GT077A		0.848
GT078A		0.635
GT079		0.524
GT080		0.651
GT081		0.395

213 线密度仅供参考, 出货以实际磅重为准!

HD太阳能系列型材图 国家免检

新图号 旧图号	简 图	线密度 kg/m
GT082		0.245
GT083		0.267
GT084		0.519
GT085		0.646
GT086		0.674
GT087		0.655

新图号 旧图号	简 图	线密度 kg/m
GT088		0.677
GT089		0.558
GT091 角钢为 GT092		0.580
G791		
GT092		0.967
G792		
GT093 角钢为 GT094		0.832
GT094		1.519

线密度仅供参考，出货以实际磅重为准！ **214**

Applications:

Competitive Advantage:

In addition to high quality ,we at Hentec office offer customer complete service .Our aluminum solar frame comes with a 15 year warranty .Maintenance service is also available .



+86-13861643436



aluminum@hentec.com.cn



aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421