



Portable Solar Panel Aluminum Frame Solar Ground Mount Frame

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: Packed with EP ,Carton ,Pallet or wooden case
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 3000tons each month



Product Specification

- Product Name: Aluminum Solar Panel Frame
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T4, T5, T6
- Highlight: **anodized aluminum frame,
solar panel aluminum frame**

Product Description

Portable Solar Panel Aluminum Frame Solar Ground Mount Frame

Product Description

Solar panels (photovoltaic modules) aluminum frame

A. Solar module aluminum frame Size Description:

- 1) 17 * 17, 20 * 20, 23 * 17, 25 * 25, 28 * 25mm, etc., suitable for solar street lamps and other small solar power generation equipment;
- 2) 30 * 25, 35 * 30mm, suitable for 30-100W solar modules;
- 3) 35 * 35mm, suitable for 80-180W solar modules, length is generally 1580 * 808mm (the most common frame size);
- 4) 40 * 35mm, suitable for 120-200W solar modules, length is generally 1580 * 808mm;
- 5) 45 * 35mm, suitable for 180-250W solar modules, length is generally 1580 * 808 and 1650 * 992mm;
- 6) 50 * 35mm, suitable for 200-300W solar modules, length is generally 1650 * 992 and 1960 * 992mm;
- 7) Many other customized according to customer's special sizes, such as 40 * 28mm, 40 * 30mm, 42 * 35mm, 46 * 30mm, 46 * 35mm, 46 * 40mm, 46 * 50mm, 46 * 60mm, 60 * 35mm and so on.

B. Two types:

- 1) 90 Angle (screw border)
- 2) 45 corner (Corner Borders)

C. Surface treatment:

- 1) Anodized (silver, bronze, black, gold, silver, other colors)
- 2) Electrophoresis
- 3) powder coating, PVDF, polishing, sand blasting

Standard: GB/T5237 - 2004, Q/320281PDW01-2008

Size: According to your design drawings, model

Note: 1. Various sizes for our existing solar frame, without open new mold.

2 aluminum frame is very popular in Europe.

3. We can follow your design drawings requirements.



Our Advantages!

1. 22 years' experiences of manufacturing .
2. STRONG R&D: Help customers finalize the design, strong tool design ability, excellent pressing and surface treatment technology.
3. Strict quality management: ISO Administration system.
4. 24 hours on-line communication. Professional, Patient, Flexible.
5. High capacity of manufacturing and wide range of products.
6. Be able to provide secondary fabricating.
7. Small order is accepted.
8. Be able to provide one-stop supply solution.
9. Multiple payment methods: TT, LC, DP, OA.

新图号 旧图号	简 图	线密度 kg/m	新图号 旧图号	简 图	线密度 kg/m
GT001 G701		0.987	GT007 G007		0.803
GT002 角码为GT001 G702		0.530	GT008 G008		0.633
GT003 G795		0.615	GT009 G009		0.494
GT004 G794		0.466	GT010 G010		0.496
GT005 G590		0.814	GT011 G011		0.388
GT006 G591		0.681	GT012 G012		0.290







新图号	简 图	线密度 kg/m	新图号	简 图	线密度 kg/m
旧图号			旧图号		
GT013		0.372	GT019		0.665
G778			G599		
GT014		0.367	GT020		0.400
G594			G846		
GT015		0.183	GT021		0.884
G595			Z081		
GT016		0.248	GT022		1.228
G596			Z082		
GT017		0.534	GT023		0.952
G597			Z083		
GT018		0.339	GT024		1.073
G598			Z084		







线密度仅供参考，出货以实际称重为准！ 210

新图号 旧图号	简图	线密度 kg/m	新图号 旧图号	简图	线密度 kg/m
GT025 角码为GT026 G895		0.653	GT031 G893		0.548
GT026 G896		0.732	GT032 G894		0.279
GT027 角码为GT026 G915		0.424	GT033 G913		1.711
GT028 角码为GT026 G916		0.524	GT034 角码为GT033 G914		0.745
GT029 G822		1.300	GT035 G222		0.398
GT030 角码为GT029 G823		0.567	GT036 G224		0.754

新图号 旧图号	简 图	线密度 kg/m	新图号 旧图号	简 图	线密度 kg/m
GT037 G229		0.172	GT052		0.728
GT038 G230		0.374	GT054 角码为GT052		0.509
GT039 G889		0.626	GT055 角码为GT052		0.537
GT040 G888		0.756	GT061		0.161
GT041 角码为GT026 G187		0.692	GT062		0.340
GT042 角码为GT026 G789		0.443	GT063		0.209

线密度仅供参考，出货以实际磅重为准！ 212

新图号	简图	线密度 kg/m
旧图号		
GT064		0.394
GT068		0.497
GT069		0.613
GT070		0.312
角码为 GT050		
GT071		0.687
GT072		0.378

新图号	简图	线密度 kg/m
旧图号		
GT076		0.698
角码为 GT050		
GT077A		0.848
GT078A		0.635
GT079		0.524
GT080		0.651
GT081		0.395

213 线密度仅供参考, 出货以实际磅重为准!

HD太阳能系列型材图 国家免检

新图号	简图	线密度 kg/m
旧图号		
GT082		0.245
GT083		0.267
GT084		0.519
GT085		0.646
GT086		0.674
GT087		0.655
GT088		0.677
GT089		0.558
GT091		0.580
角钢为 GT092		
G791		
GT092		0.967
G792		
GT093		0.832
角钢为 GT094		
GT094		1.519

线密度仅供参考，出货以实际磅重为准！ **214**

Applications:

- 1) Living house and home building.
- 2) Commercial building, factory, shopping mall, school, stadium etc.
- 3) Power station, field operation and some huge engineer construction.

Competitive Advantage:

In addition to high quality ,we at Hentec office offer customer complete service .Our aluminum solar frame comes with a 15 year warranty .Maintenance service is also available .



HENTEC Hentec Industry Co.,Ltd

+86-13861643436

aluminum@hentec.com.cn

aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421