



Powder Painted Aluminium Glass Sliding Doors / Aluminum Window Frame Extrusions

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: EP Paper ,kraft and pallet
- Delivery Time: 20days
- Payment Terms: T/T or L/C
- Supply Ability: 100 000 ton each month



Product Specification

- Material: Aluminum Alloy
- Temper: T5 / T6
- Alloy: 6063 / 6061 / 6060
- Surface: Powder Painted
- Color: Customerized
- Highlight: **aluminum extrusion profiles,
extruded aluminium profiles**



Product Description

Feelingtop Excellent Aluminum Window Extrusion Profiles / Soundproof Double Layer Tempered Glass Silding Window / Door

Specification of Aluminum Sliding Door

Brand	HTNTEC	
Dimension	Standard or OEM	
Opening Style	Horizontal Sliding	
Surface Finishing	Finished	
Profile	Sort	Extrusion profile, thermal-break , aluminum alloy
	Thickness	2.0mm Profile thickness
	Color	Cherry wood/ red sandalwood/ mahogany/ white oak/ golden oak/ white/ sand-lime/ fluorocarbon luxury gold/ fluorocarbon champagne gold/ fluorocarbon silver black etc.
Glass	Type	Customized (Hollow toughened glass/ Laminated Glass etc)
	Sealing	Neutral Silicone Sealant
Hardware	Color	Silver, Gold, White, Black etc.
	Sealant	EPDM
Cert	Production Standard	ISO9001:2008
	Profile Standard	GB 5237.6-2004
Packing	1. Wooden Crate+EPE Foam+Paper Angle Protector	
	2. Customized package	

Feature of Aluminum Door

1. Heat insulation, soundproof, anti-Theft, decoration, good sealing performance, space and energy saving, easy to install and clean , economical and easy to maintenance, high decay resistance, high strength
2. The upglide adopts relief step structure, and the glide adopts cant stair structure, easy to open and close, flexibly and freely.
3. Apply to luxury villa, hotel, residence, large store, project and various kinds of large spaces.



Specifications:

1. Primary Technical Data

1) Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest

6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

Competitive Advantage:

1. Top Aluminium profile manufacturer for more than 10 years in China.
2. Diverse Products used in the fields of construction, industry and deep-processing.
3. Quality Control is put in the core position of our production.
4. Customized Production shows our capability in product design and process control.
5. Perfect Customer Services include careful packaging, quick delivery and good after-sale service.



Tag :

aluminium window extrusion profiles

powder coating aluminium window frames

HENTEC Hentec Industry Co.,Ltd

+86-13861643436 aluminum@hentec.com.cn aluminuextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421

