



Anodized Aluminium Door Profiles , European Standard Aluminium Door And Window Frames

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 1 ton
- Packaging Details: EP Paper ,kraft and pallet
- Delivery Time: 20days
- Payment Terms: T/T or L/C
- Supply Ability: 100 000 ton each month




Product Specification

- Material: Aluminum Alloy
- Temper: T5 / T6
- Alloy: 6063 / 6061 / 6060
- Surface: Powder Painted
- Color: Customerized
- Highlight: **extruded aluminium profiles,
profile aluminum extrusions**



More Images



Product Description

Description:

Anodized Aluminium Door Profiles , High Quality /European Standard Winodiw / Door

Material :6063

Surface : Mill Finished, Powder Coating ,Chemical and Mechanical Polishing, Sand Blasting , Satin, Bronze, Black, Golden, Silver, Anodizing, Electrophoresis

MOQ :10 sets .

Packing : EPE, wrapped with waterproof paper ,pallet ,wooden case .

Sample delivery time : Two weeks

Specifiaction of High Quality Aluminum Profile:

Description	aluminum profile windows and door
Material Thickness(t)	t=1.0 / 1.2 / 1.4
Material	Aluminum Alloy 6063, 6061
Annealing Treatment	T5,T6
Color	Green, Grey, Black, White, (RAL series)etc.
Surface Treatment	Mill finish, anodized, powder coated, electrophoresis, sand balsting etc.and depend on customer's demand.
Shape	Square, Round, Flat, Oval, and according to customer's drawing.
Length	Normal length=6m or in customer's request
Usage	Building, Production Line, Decoration, Industrial, Transportation, Door and window, etc.
Package	1. Pearl cotton foam for each aluminum profile ; 2. Wrap with shrink film exterior; 3. Packed according to customer request.
Advantages/Features	Providing colorful products with various mechanical performances to adapt all kinds of architectural styles

Applications:

Aluminum profile used for making aluminum door .There are many colors can be selected for surface treatment .The strength can be increased by higher wall thickness . It is possible to produce according to customized design .



Specifications:

1. Primary Technical Data

1) Chemical composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

Competitive Advantage:


1. Top Aluminium profile manufacturer for more than 10 years in China.
2. Diverse Products used in the fields of construction, industry and deep-processing.
3. Quality Control is put in the core position of our production.
4. Customized Production shows our capability in product design and process control.
5. Perfect Customer Services include careful packaging, quick delivery and good after-sale service.



Tag :
aluminium window extrusion profiles
,
powder coating aluminium window frames

 **HENTEC** Hentec Industry Co.,Ltd

 +86-13861643436

 aluminum@hentec.com.cn

 aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421