



Anodized Industrial Aluminium Profile Electrical Cover / Electrical Shell

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Hentec
- Certification: SGS
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



Product Specification

- Product Name: Industrial Aluminium Profile
- Alloy: 6063,6061
- Material: Aluminum
- Surface Treatment: ,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T5, T6
- Highlight: **aluminium door frame,
aluminium extruded profiles**



Product Description

Description: Anodized Industrial Aluminium Profile Electrical Cover / Electrical Shell

Hentec Industrial Co., Ltd is professional serves for Building doors and windows profiles, Railway, Cars with aluminum, IT computer, Communications, Electrical, Mechanical, High-speed rail transportation, Refrigerated containers etc., special aluminum profiles for 17 years.

- 1 Business type: Real Big Manufacturer & Exporter with 17 years experience
- 2 Production Standard: Architecture Profile : GB 5237-2008
Industry Profile : GB/T6892-2008
- 3 Main products: Aluminum extrusion profiles for architectural & industrial, Different aluminum profile sections for different applications.
Aluminum Formwork for Building Construction.
 1. Mould / Tooling analysis, design & manufacturing
 2. Mould / Tooling testing & confirm the sample
 3. Die-casting rough parts
- 4 Manufacture Process:
 4. Precision machining: CNC lathes, milling, drilling, grinding etc
 5. Surface treatment: Trimming, polishing, cleaning, passivation & power coating and other requirement from Customer
 6. Full Inspection
 7. Packing
- 5 Price: Aluminium Ingot price + different finishes processing Fee + local cost
- 6 Payment term: T/T, L/C at sight
 - A. Alloy: 6063, 6060, 6061, 6005 etc
 - B. State: T5/T6
 - C. Length: 1m-13 m (polishing : 2.5 m)
 - D. Normal Anodizing thickness: 8-12 micro
- 7 Specification:
 - E. Normal powder coating thickness: 60-100 micro
 - F. Tensile strength: ≥ 16 mpa
 - G. Yield strength: ≥ 110 mpa
 - H. Extensibility: $\geq 8\%$
 - I. Hardness(HW): ≥ 8
- 8 Packing: Kraft paper, EPE Fram, Shrink film, Carton Box, Wooden box etc, Customized package is available.
- 9 MOQ: 1X20 FCL, Each profile not less than 500 kgs. Each color not less than 2 tons.
- 10 Sample time: 10-15 days after drawing confirmed and mold cost paid.
- 11 Delivery time: 35 days after deposit received.
- 12 Port: Shanghai Port

Order, payment, terms, shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days (15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.) Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment: (Can negotiate with customers, our usual practices are as follow)
- 4, Tooling: 100% prepaid by T/T.
- 5, Parts: 30% upon order confirmation and balance before delivery by T/T

Applications:

Aluminum profile used in cars, trains machinery, electronics, medical and other industrial filed. In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.