



Powder Painted / Anodized Industrial Cooling Blade / 16ft Large Blade Ceiling Fan

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: HT
- Certification: CA ,CE
- Minimum Order Quantity: 500set
- Packaging Details: Ep paper , pallet or wooden case
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000sets each month



Product Specification

- Product Name: Industrial Fan Blade
- Item: Aluminum Extrusion Profile Of Industrial Fan Blade
- Temper: T5, T6 ,T66
- Surface: Powder Painted
- Material: Aluminum
- Machining: 1. Milling; 2. Drilling; 3. Bending; 4. Cutting
- Highlight: **replacement fan blade, exhaust fan blades**



Product Description

Powder Painted / Anodized Industrial Cooling Blade / 16ft Large Blade Ceiling Fan

Description:

Powder Painted / Anodized Industrial Fan Blade / Cooling Blade / 16ft Large Blade Ceiling Fan

Our Aluminum profiles for Large HVLS fans are widely applied in livestock barns, warehouses, distribution centers, shopping malls, skating rinks health clubs and so on. Due to the rising costs of energy, Large HVLS fans are often used to supplement HVAC systems as they provide a stronger cooling effect while helping to maintain a constant temperature and humidity.

A. Design and manufacture profiles of all sizes
B. Alloy: 6063/6061/6005/6060 T5/T6 are available
C. Finish: Anodizing, powder coating, wood clour(timber turning), polishing, brushed, mill finish available
D. Procedure: Preciously Cutting, milling, drilling, punching, CNC machining
E. OEM is welcome
Why we are your best choice:
• Reliable quality (ISO 9001:2000-certified).
• Competitive prices with short lead-time for both tooling and parts,
• we do everything in-house.
• Effective and strong technical supp commercial aluminum window frames ort and excellent sales service.
• Sufficient production capacity (only aluminum frame stage with plywood platform 6 aluminum frame structure aluminum frame carry-on luggage 5% occupied) rust-free aluminum frames .
• Efficient communication (48-hour q anodized aluminum picture frame uote lead time).

Specifications:

1. Primary Technical Data

1) Chemical composition

2) Mechanical property

Alloy	Temper	Tensile strength	Yield strength	Elongation
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%
	T6	≥ 205Mpa	≥ 180Mpa	≥ 8%
6061	T6	≥ 265Mpa	≥ 245Mpa	≥ 8%

3. Surface Treatment of Sections

(Class)	(μm),not diminish than		acid-resistant			abrasion re sistance
	(Min- average fil m thickness)	(Min- part film thickness)	CASS		(S)	(f, g /μm)
			(h)	Class		
AA10	10	8	16	≥9	≥50	≥300
AA15	15	12	32	≥9	≥75	≥300
AA20	20	16	56	≥9	≥100	≥300
AA25	25	20	72	≥9	≥125	≥300

Competitive Advantage:

- 1.High hardness, hard aluminum series.
- 2.Fair corrosion resistance. Heat treatable
- 3.Good workability. Good appearance
- 4.High quality and reasonable price.
- 5.Our product is your best choice.



HENTEC Hentec Industry Co.,Ltd

+86-13861643436

aluminum@hentec.com.cn

aluminumextrusion-profiles.com

Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421