Aluminum Window Extrusion Profiles, Sliding Glass Door Channel Door **Bottom Twin Track**

Basic Information

- Place of Origin:
- Brand Name:
- CA ,CE Certification:
- Minimum Order Quantity: 1 ton
- Packaging Details: EP Paper ,kraft and pallet

China

HT

- Delivery Time:
- Payment Terms:
- Supply Ability:



100 000 ton each month

Product Specification

• Material: • Temper:

• Alloy: • Surface: Aluminum Alloy T5 / T6 6063 / 6061 Anodized

Customized

- Colour:
- Application:
- Highlight:
- Window aluminum extrusion profiles, extruded aluminium profiles

Our Product Introduction



Product Description

T Track Aluminum Window Extrusion Profiles ,Sliding Glass Door Channel Door Bottom Twin Track

Description :

- 1. Suitable for industry, architecture, transportation and so on.
- 2.20 years warranty.
- 3.High corrosion resistance.
- 4.5-10 years weather resistance.
- 5.Good wear resistance & anti-scratch.

6.Size customized.

Alloy:	6063	6061	6060	6005	6082				
Temper :	T5	Т6	T4		_				
Standard:	DIN	AAMA	AS	CHINAGB					
Certification:	ISO9001:2008.	1	1	1	1				
Surface Finish:	Mill finish	Anodizing	Powder Coating	Wood Grain	Electrophor esis	Polished	Brushed		
Color:	Anodizing:	Silver, bronze, champagne, titanium, nickel, golden yellow, etc.							
		Anodizing thickness is up to 25um.							
		White, black,	bronze, grey	green, etc .					
	Powder Coating:	Powder coating thickness is more than 60um.							
		1.Italian MENPHIS transfer printing paper.							
		2.AKZO NOBEL INTERPON D1010(10 years warranty):Australia ceder, Bush cherry, Chest nut, Jarrah I, Jarrah II, Western red ceder, etc.							
	Wood Grain:	3.AKZO NOBEL INTERPON D34(5 years warranty):Bush wood, Western red, Jarrah, Snow gum, etc.							
	Electrophoresis:	Silver, nickel, golden yellow, black, champagne, etc							
	Polishing	Silver, nickel, golden vellow, black, etc							
	Brushing:	Silver, nickel, golden yellow, black, bronze, etc							
Machining:	Cutting, punching	g, drilling, bending, weld, mill, CNC, etc.							
OEM customized	aluminium profiles are	available.							

Applications:

Aluminum profile used for making aluminum door . There are many colors can be selected for surface treatment . The strength can be increased by higher wall thickness . It is possible to produce according to customized design .



Specifications:

1. Primary Technical Data 1) Chemical composition

r) Chemical composition										
Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Impurity	Al
6063	0.2-0.6	0.35	0.1	0.1	0.45-0.9	0.1	0.1	0.1	0.15	Rest
6061	0.4-0.8	0.7	0.15-0.4	0.15	0.8-1.2	0.04-0.35	0.25	0.15	0.15	Rest
6060	0.3-0.6	0.1-0.3	0.1	0.1	0.35-0.6	-	0.15	0.1	0.15	Rest
6005	0.6-0.9	0.35	0.1	0.1	0.40-0.6	0.1	0.1	0.1	0.15	Rest

2) Mechanical property

Alloy	iiomnor	Tensile strength	Yield strength	Elongation	
6063	T5	≥ 160Mpa	≥ 110Mpa	≥ 8%	
0000	Т6	≥ 205Mpa	≥ 180Mpa	≥8%	
6061	Т6	≥ 265Mpa	≥ 245Mpa	≥8%	

Competitive Advantage:

- 1. Top Aluminium profile manufacturer for more than 10 years in China.
- 2. Diverse Products used in the fields of construction, industry and deep-processing.
- Quality Control is put in the core position of our production.
 Customized Production shows our capability in product design and process control.
- 5. Perfect Customer Services include careful packaging, quick delivery and good after-sale service.



Tag : aluminium window extrusion profiles , powder coating aluminium window frames



+86-13861643436 aluminum@hentec.com.cn aluminumextrusion-profiles.com Qinfeng Road No.555 Huashi Town Jiangyin Jiangsu China (mainland) 214421