



Industrial Aluminium Extruded Profiles Aluminium Deep Processing Profiles

Our Product Introduction

for more products please visit us on aluminumextrusion-profiles.com

Basic Information

- Place of Origin: China
- Brand Name: Hentec
- Certification: SGS
- Minimum Order Quantity: 1 ton
- Packaging Details: Ep paper ,kraft ,pallet
- Delivery Time: 20days
- Payment Terms: T/T ,L/C
- Supply Ability: 100 000ton each month



Product Specification

- Product Name: Industrial Aluminium Profile
- Alloy: 6063,6061,6005
- Material: Aluminum
- Surface Treatment: Mill Finished,Anodized ,Electrophoretic Coated,Powder Spray Coated
- Deep Process: Milling, Drilling, Bending,Cutting
- Temper: T4, T5, T6 ,T66
- Highlight: **aluminium extruded profiles,
aluminum extruded shapes**

Product Description

Industrial Aluminum Extrusion Profile Aluminium Deep Processing Profiles

Hentec Industry Co.,Ltd is one China Manufactory, professional at aluminum extrusion profiles, both semi and final products, such as LED aluminum bracket, aluminum door, aluminum window, aluminum curtain rod, aluminum guide rail, aluminum fencing and all kinds of industrial and building aluminum profile, square, round, flat, oval, angle, irregular and all types according to the customers' drawing.

Features:

1. Adopt 99.7% aluminum ingots as raw material.
2. Reasonable price and good quality.
3. Mill finish, anodized, powder coated, electrophoresis, sand blasting etc. and depend on customer's demand.

Terms:

1. Payment terms: T/T, L/C
2. Terms for Delivery: Ex-work, FOB, CIF
3. Samples of aluminum profile sent within 10 days
4. Lead time is 15-20 days.
5. Aluminum Profile Monthly production capability is 4000 tons.

Description	Aluminum profile, Aluminium extrusion
Material Thickness(t)	t=0.3 / 0.6/ 0.8/ 0.9/1.0 / 1.2 / 1.4
Material	Aluminum Alloy 6063, 6061, 6060
Annealing Treatment	T5, T6
Color	Silver, Green, Grey, Black, White, (RAL series) etc.
Surface Treatment	Mill finish, anodized, powder coated, electrophoresis, mechanic polishing, chemical polishing, sand blasting etc. and depend on customer's demand.
Shape	Square, Round, Flat, Oval, and according to customer's drawing.
Length	Normal length=5.85m, 5.98m, 5.95m or in customer's order
Usage	Building, Production Line, Decoration, Industrial, Transportation, Door and window, etc.
Package	1. Pearl cotton foam for each aluminum profile ; 2. Wrap with shrink film exterior; 3. Packed according to customer request.
Advantages/Features	1. Providing colorful products with various mechanical ; 2. Performances to adapt all kinds of architectural styles

Order, payment, terms, shipment

- 1, Minimum order: 500kg per trial order 1 piece of sample free of charge provided by approval and kept for future mass production.
- 2, Sample Lead Time: 25 working days (15 days for making the tool and 10 days making the samples. Before sending the samples to customer, samples should pass strict test in our lab.) Production Lead time: it depends on customers' order quantity (30 working days after deposit).
- 3, Payment: (Can negotiate with customers, our usual practices are as follow)
- 4, Tooling: 100% prepaid by T/T.
- 5, Parts: 30% upon order confirmation and balance before delivery by T/T

Applications:

Aluminum profile used in cars, trains machinery, electronics, medical and other industrial filed. In terms of hardware, machinery, electromechanical parts, solar PV products, aluminum frames are adopt as important auxiliary materials. We also have aluminum profiles for radiators, fitness machinery, buildings, lighting instrument, windpipes, oil pipelines, for instance.

Competitive Advantage:

1. good quality aluminium profile with economic price
2. 15-year manufacturing experience
3. ISO9000
4. ODM or OEM



FAQ For Saving Your Precious Time!

Q1: What's the thickness for anodizing? Can you do 15um?

A: Our normal thickness is about 10 um. Yes, we can do 15um and above.

Q2: What color you can do for powder coating? The thickness for powder coat?

A: We can do any color for powder coat as long as you can provide the color sample. Our normally powder coating thickness is 60-80um.

Q3: What color you can do for wood grain?

A: Our most popular colors are Western Red Cedar, Australia Cedar, Jarrah I, Jarrah II, Chestnut, Bush Cherry, Bush Wood, Western Wood, Snow Gum, etc. If you need any other colors, we can do according to the color samples you provide.

Q4: How's the weather resistance for wood grain finish D1010?

A: (1). Powder: Akzo Noble Interpon D1010.

(2). Wood grain film: Italian Memphis.

(3). Standard complied: American AAMA Standard.2603

(4). UV test: 1000 hours.

(5). Salt spraying test: 1000 hours.

(6). Normal weather: 10 years color guarantee.

Q5: What certification do you have? What's your standard?

A: We have ISO certification. Our standard is DIN, AAMA, AS/NZS, China GB.

Q6: What's the delivery time for samples and mass production?

A: (1). 2-3 weeks to make the new moulds and make free samples.

(2). 3-4 weeks after receipt of deposit and confirmation of the order.